

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Pg. 2680)

A point, 125 ft. above stream, I set a Maple post, 3 ft. long, 4" sq., 24" in ground, for cor. to secs. 21, 22, 27 & 28 marked T23S S22 on NE, R9W S27 on SE, S28 on SW, & S 21 on NW faces, with 2 notches on S & 3 notches on E edges; from which
A Fir, 24" dia. bears N.37°E., 32 lks mkd: T23S R9W S22 BT
A Fir, 36" dia. bears S.80°E., 38 lks mkd: T23S R9W S27 BT
A Fir, 24" dia. bears S.½°W., 122 lks mkd: T23S R9W S28 BT
A Fir, 30" dia. bears N.77°W., 62 lks mkd: T23S R9W S21 BT

BLM dependent resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #927, surveyed Aug. thru Nov. 1977 - (DCSO records Vol. 41 Page(s) 16211)

The cor. of secs. 21, 22, 27 & 28 determined at rec. bearing & dist. from the orig. BTs:
A Fir, 35" dia., bears N.37°E., 32 lks., with scribe marks T23S R9W S22 BT visible on bark blaze.
A Fir, 63" dia., bears S.80°E., 38 lks. with healed blaze.
A Fir, 47" dia., bears S.0½°W., 122 lks., with scribe marks T S W visible on weathered bark blaze.
A Fir, 50" dia., bears N.77°W., 62 lks., with healed blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T23S R9W
S 21 | S 22
S 28 | S 27
1977