

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2686)

-----  
A point, 150 ft. above stream, I set a Hemlock post 3 ft. long, 3" sq. 24" in the ground, for ¼ sec. cor., marked ¼ S16 on W. face, 15 on E face, from which:

- A Hemlock, 6" dia., bears N.83°E., 19 lks., mkd: ¼ S15 BT.
- A Hemlock, 24" dia., bears N.10°W., 54 lks. mkd: ¼ S16 BT.

BLM remonumentation by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed Aug. 1960 - (DCSO records Vol. 30 Page(s) 12890)

-----  
The ¼ sec. cor. of secs. 15 & 16 determined at the record bearing & distance from each of the orig. BTs, as follows:

- A Hemlock snag, 30" dia., bears N.10°W., 54 lks., with scribe marks ¼ S16 BT visible on unhealed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:

¼  
S 16 | S 15  
T23S R9W  
1960

from which

- A Hemlock, 13" dia., bears S.4°E., 126 lks. mkd: ¼ S15 BT.
- A Fir, 6" dia., bears S.67½°W., 79 lks., mkd: ¼ S16 BT.

Fd. Ok by DCSO, Gary Langlitz, 2/10/1975 - C.S. File 57/17-17