TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2659)

Set a Hemlock post,3 ft. long, 4" sq., 24" in ground, for cor. to secs. 9, 10, 15, & 16 marked T23S S10 on NE, R9W S15 on SE, S16 on SW, & S9 on NW faces, with 4 notches on S and 3 notches on E edges; from which

A Fir, 40" dia., bears N.05°E., 46 lks., mkd: T23S R9W S10 BT.

A Fir, 60" dia., bears S.72°E., 108 lks., mkd: T23S R9W S15 BT.

A fir, 6" dia., bears S.32°W., 19 lks., mkd: T23S R9W S16 BT.

A Fir, 36" dia., bears N.24°W., 63 lks., mkd: T23S R9W S9 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - V. Peron - June 1970 - C.S. File 54/60-51

Found - Orig. 40" Fir, now stump, N.5°E., 30.4 ft., no scribe, found bark gone.
Orig. 36", now 40" Fir stump, N.24°W., 41.6 ft., old axe blaze, possible fragmentary scribe on bark.
Orig. 60" now 64" Fir stump, out of place, S.72°E., 71.3 ft., fragmentary bark scribe.
Orig. BT to SW gone.
Calls E - W & S to ridge tops fit old field notes good.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1970

T23S	R9W
S 9	S 10
S 16	S 15

Remarked

OBTs - 40" Fir stump N.24°W., 41.6 ft., mkd: T23S R9W S9 CS BT
40" Fir stump N.5°E., 30.4 ft., mkd: T23S R9W S10 CS BT
No live trees available - Line tag on road to S of cor.
3/4" iron rod S.61°E., 20.0 ft.
3/4" iron rod S.74°W., 15.0 ft.