TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2687-8)

A point 350 ft. above stream, I set a Fir post,3 ft. long, 4" sq., 24" in ground, for cor. to secs. 3, 4, 9, & 10 marked T23S S3 on NE, R9W S10 on SE, S9 on SW, & S4 on NW faces, with 3 notches on E and 5 notches on S edges; from which

A Fir, 36" dia., bears N.10°E., 45 lks., mkd: T23S R9W S3 BT.

A Fir, 30" dia., bears S.8°E., 35 lks., mkd: T23S R9W S10 BT.

A Fir, 30" dia., bears S.89°W., 56 lks., mkd: T23S R9W S9 BT.

A Fir, 18" dia., bears N.46°W., 20 lks., mkd: T23S R9W S4 BT.

Douglas Co. Surveyors Office - Larry E. Monrean - 10/9/1973 - C.S. File 56/39-13

Found - 36" now 48" Fir, N.10°E., 29.7 ft., scribed T2 R9W
18" now 24" with double bottom Fir, N.46°W., 13.2 ft., find no scribing.
30" Fir S.89°W., 36.1 ft., find blaze, no scribing.
30" Fir stump S.8°E., no scribing.

Set - Brass cap mkd: COUNTY SURVEYORS OFFICE 1973 T23S R9W

S 4	S 3
S 9	S 10

10" Hemlock bears S.66°W., 50.4 ft., mkd: T23S R9W S9 CS BT
8" Hemlock bears S.18°E., 29.8 ft., mkd: T23S R9W S10 CS BT
Rescribed 24" Fir bears N.46°W., 13.2 ft., mkd: T23S R9W S4 CS BT

Corner is approx. 200 ft. north on line, and on the NW side of slope running SW.

Stephen D. Waite, LS 1374 - For: International Paper - 12/28/1977 and 1/4/1978 - C.S. File 58/159

12/28/1977

Found - 3/4" IP without cap.
48" Fir stump N.10°E., 29.7 ft. no scribing.
24" double bottom Fir stump N.46°W., 13.2 ft., scribed BT.
10" Fir stump, uprooted, scribed as described by County Surveyor 10/9/1973 as 10" Hemlock S.66°W., 50.4 ft. (1973)

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

36" Fir stump S.89°W., 36.1 ft. no scribing.
Set - 1½" x 30" pipe with 2½" brass cap mkd: T23S R9W

S 4	S 3
S 9	S 10

Sec. Cor. 1977 PLS 1374

1/4/1978
BTs rescribed -
48" Fir N.10°E., 29.7 ft., mkd: T23S R9W S3 CS BT
24" double bottom Fir stump N.46°W., 13.2 ft., mkd: T23S R9W S4 CS BT
36" Fir stump S.89°W., 36.1 ft., mkd: T23S R9W S9 CS BT
New BT - 36" Fir stump S.47°E., 45.5 ft., mkd: T23S R9W S10 CS BT