TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2690-1)

A point, 120 ft. above last stream, I set a Hemlock post, 3 ft. long, 3" sq. 24" in the ground for ¼ sec. cor. mkd: ¼ S4 on W face, 3 on the E face, from which:

A Fir, 50" dia., bears S.33°W., 13 lks., mkd: ¼ S4 BT.
A Fir, 48" dia., bears S.35°E., 46 lks., mkd: ¼ S3 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - V. Perron - June 1970 - C.S. File 54/60-56

Not found
Logged & burned last year or so.

Douglas Co. Surveyors Office - Larry E. Monrean - P. L. Earle - Oct. 1973 - C.S. File 56/39-12

Found - 50" Fir, now 7 ft. bark scribed ¼ S4 BT bears S.33°W., 8.6 ft.
48" Fir snag, bears S.35°E., 30.4 ft. no scribing, bark gone.

Set - Brass cap mkd: COUNTY SURVEYORS T23S R9W
OFFICE ¼
1973 S 4|S 3
18" Hemlock, bears S.54°E., 8.2 ft. scribed T23S R9W S3 CS BT.

BLM resurvey by Joseph M Mannix & Edith M Forkner, Cadastral Surveyors Under group No. 2727 surveyed Oct. 2013/April 2014 - (DCSO records Vol. 58 Page(s) 23224)

The ¼ sec. cor. of secs. 3 & 4, perpetuated by the Douglas County Surveyor's Office, in 1973; monumented with an iron post, 1¼" dia., firmly set, projecting 13" above ground, with a brass cap (properly) mkd.
from which the remains of the original bearing trees

A fir snag, 48" dia., bears S.35°E., 30.4 ft., no marks visible.
A fir, 84" dia., bears S.33°W., 8.6 ft., with a healed blaze.

and a BT mkd. by the Douglas County Surveyor's Office

A hemlock, 18" dia., bears S.54°E., 8.2 ft., with a healed blaze.