

PRIMARY CORNER DESCRIPTION Cor. Secs 26, 27, 34, & 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 survey by Oscar F. Thiel, Deputy Surveyor under contract # 688, dated June 9, 1898 - (DCSO rec. Vol. 6 Page(s) 2650-1)

A point 75 ft. above stream, I set an Alder post, 3 ft. long, 4" sq. 24" in the ground, for cor. of secs. 26, 27, 34 & 35, mkd: T23S S26 on NE; R9W S35 on SE; S34 on SW; and S27 on NW faces, with 1 notch on S & 2 notches on E. edges, from which
 An Alder, 10" dia., bears N.53°E., 7 lks., mkd: T23S R9W S26 BT.
 A Hemlock, 6" dia., bears S.51½°E., 47 lks., mkd: T23S R9W S35 BT.
 A fir, 8" dia., bears S.5°W., 8 lks., mkd: T23S R9W S34 BT
 A Fir, 12" dia. bears N.68°W., 43 lks mkd: T23S R9W S27 BT

Donald Peel - For: Weyerhaeuser Co. - March 1967 - C.S. File 55/30-3

Found - GL0 record post - gone.
 10" Alder N.53°E., 7 lks., now gone.
 6" Hemlock S.51½°E., 47 lks., now 8" Hemlock stub, rotted off below scribe.
 8" Fir s.5°W., 8 lks., now 17" Fir stub broken off below scribing; scribing visible on downed part of log.
 10" Fir, N.68°W., 43 lks, now 22" Fir snag - face visible - healed over - cruisers marks.
Set - 4' x 3/4" pipe & sq. post, re-referenced with "W" nail & Weyerhaeuser tags:
 28" Fir N.62°E., 25.4 ft.
 22" Hemlock S.47°E., 38.5 ft.
 27" Hemlock S.5°W., 14.5 ft.
 17" Hemlock N.45°W., 31.4 ft.

Tony Hostetter - For: Weyerhaeuser Co. - Dec. 2011 - C.S. File 65/76-5

Found - 1/2" Alum. pipe, listed as 3/4" by Peel in 1967
 22" Fir stump, orig. BT, WEYCO tag, bears N.68°W., 28.4 ft. to center.
 28" Fir snag, Peel BT (C.S. 55/30) WEYCO tag, bears N.67°E., 26.3 ft. to center.
New BTs- 16" Fir scribed "S26 SW BT" WEYCO tag, bears N.24°E., 4.3 ft. to spike in root collar.
 12" Fir scribed "S34 NE BT" WEYCO tag, bears S.65°36'W., 17.6 ft. to spike in root collar.
 14" Fir, scribed "S27 SE BT" WEYCO tag, bears N.53°15'W., 40.4 ft. to spike in root collar.

cont.

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor Secs 26, 27, 34, & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23301)

The cor. of secs. 26, 27, 34, & 35, perpetuated by Peel, in 1967 and further perpetuated by Hostetter, in 2011; monumented with an aluminum pipe, 1/2" dia., firmly set, projecting 6" above ground, from which the remains of an original bearing tree

A decayed fir stump, 18" dia., bears N.68°W., 28.4 ft., with axe marks visible on open decayed blaze.
and the remains of the bearing trees mkd. by Peel

A decayed fir snag, 29" dia., bears N.67°E., 26.8 ft., with a healed blaze.

A root hole bears S.5°W., 14.5 ft., alongside of which is a down decayed hemlock high stump, 24" dia., no marks visible.

A hemlock stump, size indeterminate, bears N.45°W., 32.3 ft., no marks visible. Decayed remains of tree alongside.

and the bearing trees mkd. by Hostetter

A fir, 14" dia., bears N.18½°E., 5.2 ft., with illegible scribe marks visible on partially healed blaze and a nail at the base on the front center.

A fir, 15" dia., bears S.65¼°W., 18.4 ft., with illegible scribe marks visible on partially healed blaze and a nail at the base on the front center.

A fir, 18" dia., bears N.63°W., 41.4 ft., with illegible scribe marks visible on partially healed blaze and a nail at the base on the front center.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over aluminum pipe, with brass cap mkd.

T 23 S R 9 W
S 27 | S 26
S 34 | S 35
2014

and a new bearing tree

A fir, 15" dia., bears S.20°E., 32.0 ft., mkd. T23S R9W S35 BT.

Drive an aluminum angle iron alongside the cor.

NAD 1983 (2011)

Latitude: 43°31'51.92" N Longitude: 123°44'48.66" W