

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2678)

-----

Set a hemlock post, 3 ft. long, 3" sq., 24" in ground, for ¼ sec. cor. marked ¼ S10 on W face, 11 on E face, from which

A fir, 40" dia., bears N.15°E., 28 lks., mkd: ¼ S11 BT.

A fir, 20" dia., bears N.71°W., 20 lks., mkd: ¼ S10 BT.

BLM resurvey by Joseph M Mannix & Edith M Forkner, Cadastral Surveyors Under group No. 2727 surveyed Oct. 2013/April 2014 - (DCSO records Vol. 58 Page(s) 23218)

-----

The ¼ sec. cor. of secs. 10 & 11, perpetuated during an unofficial administrative survey by the BLM, in 1977; monumented with an iron rod, 5/8" dia., firmly set, with top flush with the surface of the ground, from which the remains of the original bearing trees

A decayed fir stump, 44" dia., bears N.15°E., 18.5 ft., with axe marks.

A roothole bears N.71°W., 13.2 ft., alongside of which is a down decayed fir, 26" dia., no marks visible. and the remains of the bearing trees mkd. by the BLM

A decayed hemlock stump, 25" dia., bears N.39°E., 35.8 ft., with a spike at the base facing the cor.

A decayed hemlock stump, 33" dia., bears N.38°W., 29.2 ft., with a spike at the base facing the cor.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, directly over iron rod, with a brass cap mkd.

T23S R9W

¼  
S 10 | S 11  
2013

from which new bearing trees

A fir, 10" dia., bears N.69¼°E., 6.6 ft., mkd. ¼ S11 BT.

A fir, 9" dia., bears N.51¾°W., 19.3 ft., mkd. ¼ S10 BT

Each new bearing tree has a 2½"x1/4" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

An aluminum angle iron, 5 ft. long, was driven alongside all corners unless an existing guard post was otherwise noted in the corner description.