

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #688, dated June 9, 1898 - (DCSO records Vol. 6 Page(s) 2641)

-----  
Set a sandstone 20x10x10 ins., 15" in the ground for ¼ sec. cor., marked ¼ on N. face, from which

A Vine Maple 6" dia., bears N.12°E., 19 lks. dist., mkd. ¼ S35 BT.

A Vine Maple 5" dia., bears S.13°W., 23 lks. dist. mkd. ¼ S35 BT.

Douglas Co. Surveyors Office - J.W. Byron - (probably 1967)  
C.S. File 54/60-57

-----  
We find no original evidence of this corner.

Find "W" nail tag on 30" Fir stump, N.59°E., 52.0 ft. from 1/2" monel pipe and 30" Fir stump S.20°E., 72.0 ft. with "W" nail and tag.