

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 6 Page(s) 2650)

-----

A point 50 ft. above stream; I set a sandstone 22x12x6", 17" in the ground for ¼ sec. cor. mkd: ¼ N on face, from which:  
 A Chinquapin, 6" dia., bears S.3°E., 18 lks., mkd: ¼ S35 BT.  
 A Fir, 4" dia., bears N.64°E., 19 lks., mkd: ¼ S26 BT.

Donald Peel - For: Weyerhaeuser Co. - March 1967 - C.S. File 55/30-3

-----

Found - GLO record sandstone, found badly decomposed in upright position - no etchings on stone remaining.  
 6" Chinquapin S.3°E., 18 lks., gone.  
 4" Fir N.64°E., 19 lks., now 12" Fir windfall - chopped open - scribe visible.

Set - 4' x 3/4" pipe & square post, re-referenced with "W" nail & Weyerhaeuser tags:  
 14" Hemlock N.8°E., 23.3 ft.  
 68" Fir S.52°W., 28.2 ft.

Note - "W" nail drive into notch cut low on a tree, with dist. & bearing to "W" nail stamped on Weyerhaeuser tag. Tag nailed high on same tree.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23301-2)

-----

The ¼ sec. cor. of secs. 26 & 35, perpetuated by Peel, in 1967, from original evidence no longer in existence; monumented with an aluminum pipe, 1/2" dia., firmly set, projecting 9" above ground, from which the remains of the bearing trees mkd. by Peel  
 A decayed hemlock stump, 16" dia., bears N.9°E., 23.3 ft., with a healed blaze.  
 A fir stump, 75" dia., bears S.49°W., 28.9 ft., with a nail marked W in an axe mark.

At the corner point  
 Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over aluminum pipe, with a brass cap mkd.  
 T 23 S R 9 W  
 ¼ S 26  
       S 35  
       2014

continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which

A fir, 11" dia., bears N.27°E., 18.3, mkd. ¼ S26 BT.

A fir, 8" dia., bears S.63°W., 8.5, mkd. ¼ S35 BT.

Drive an aluminum angle iron alongside the cor.