

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 26

Alias	Description

Ronald Stuntzner - For: International Paper Co. - June 7, 1976 - M 60-41

Set - 5/8" iron rod with yellow cap.
48" D.Fir, N.51°W., 29.7 ft.
6" Hemlock, S.57½°W., 10.0 ft.
48" D.Fir, S.72°30'E., 52.2 ft.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23317)

The center ¼ sec. cor. of sec. 26, established by Stuntzner, in 1976, and is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, with a bleached plastic cap with illegible marks, from which the remains of the bearing trees mkd. by Stuntzner
A decayed fir stump, 50" dia., bears S.73½°E., 51.9 ft. , no marks visible.
A decayed fir stump, 60" dia., bears N.53½°W., 29.5 ft. , no marks visible. A fir, 14" dia., is growing out of the stump.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over iron rod, with brass cap mkd.
T 23 S R 9 W
C ¼ S 26
2014
and new bearing trees
A fir, 13" dia., bears S.26½°E., 14.0 , mkd. C¼ S26 BT.
An alder, 14" dia., bears N.8°W., 11.5 , mkd. C¼ S26 BT on bark.
Drive an aluminum angle iron alongside the cor.