

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Secs. 14 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2675)

Set a Hemlock post, 3 ft. long, 3" sq. 24" in the ground for 1/4 sec. cor. mkd: 1/4 S14 on N face and 23 on S face, from which:

- A Maple, 10" dia., bears S.40°E., 8 lks., mkd: 1/4 S23 BT.
- A Cedar, 16" dia., bears N.69 1/2°W., 45 lks., mkd: 1/4 S14 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Jan. 1970 - C.S. File 54/60

Found - Orig. 10" Maple S.40°E., 5.3 ft. down and badly decayed, frag. scribe on edges of blaze.
Orig. 16" Cedar N.69 1/2°W., 29.7 ft.. Only decayed stump 8" high log mostly decayed away, no scribe found.

Spur ridges call to E. fits record dist.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T23S R9W
OFFICE 1969 1/4 S14/S23
8" Hemlock N.72°W., 28.6 ft., mkd: 1/4 S14 CS BT.
24" D.Fir S.75°E., 22.6 ft., mkd: 1/4 S23 CS BT.

Note - This cor. lies on SW slope 80+ ft. W of top of spur.