

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2657)

-----

Set a Maple post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor. mkd 1/4 S11 on N face & 14 on S face, from which  
A fir, 80" dia., bears N.10°E., 11 lks., mkd: 1/4 S11 BT.  
A maple, 7" dia., bears S.29°W., 44 lks., mkd: 1/4 S14 BT.

BLM resurvey by Joseph M Mannix & Edith M Forkner, Cadastral Surveyors Under group No. 2727 surveyed Oct. 2013/April 2014 - (DCSO records Vol. 58 Page(s) 23216-7)

-----

Point for the 1/4 sec. cor. of secs. 11 & 14, at proportionate; there is no remaining evidence of the original cor.  
Set a stainless steel post, 28" long, 2 1/2" dia., 23" in the ground, with brass cap mkd.

T 23 S R 9 W  
1/4 S 11  
S 14  
2013

from which new bearing trees  
A fir, 15" dia., bears S.53°W., 24.4 ft., mkd. 1/4 S14 BT.  
A fir, 12" dia., bears N.11 1/4°W., 30.3 ft., mkd. 1/4 S11 BT.  
Each new bearing tree has a 2 1/2"x1/4" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.  
Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.  
An aluminum angle iron, 5 ft. long, was driven alongside all corners unless an existing guard post was otherwise noted in the corner description.