

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2621)</p> <p>-----</p> <p>Set Maple post 4" dia., 4 ft. long, 18" in ground for corner to secs. 2, 3, 10, & 11</p> <ul style="list-style-type: none">A Maple, 10" dia., bears N.89°E., 44 lks.A Maple, 5" dia., bears S.40°E., 21 lks.A Maple, 6" dia., bears S.87°W., 28 lks.A Maple, 8" dia., bears N.89°W., 27 lks.
<p>Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2677)</p> <p>-----</p> <p>Intersect E. & W. line 48 lks, W. of cor. of secs. 2, 3, 10, & 11; the post being gone & only the NE BT remaining I set a Maple post 3 ft. long, 4" sq., 24" in the ground, for cor. of secs. 2, 3, 10, & 11, marked T23S S2 on NE; R9W S11 on SE; S10 on SW & S3 on NW faces & 5 notches on S & 2 notches on E. edges, from which</p> <ul style="list-style-type: none">A Maple, 10" dia., bears S.52°W., 29 lks., mkd: T23S R9W S11 BT.A Maple, 4" dia., bears S.89½°W., 30 lks., mkd: T23S R9W S10 BT.A Maple, 5" dia., bears N.75°W., 24 lks., mkd: T23S R9W S3 BT.A Maple, 10" dia., bears N.89°E., 44 lks., mkd: T23S R9W S2 BT. OBT
<p>Jan. 25, 1899, Vol. 2 Pg. 261</p> <p>-----</p> <p>Set - Maple post, from which:</p> <ul style="list-style-type: none">A Maple 10" bears S.52°E., 29 lks.A Maple, 5" dia., bears N.75°W., 24 lks.A Maple, 4" dia., bears S.89½°W., 30 lks.A Maple, 10" dia., bears N.89°E., 44 lks. <p>In presents of S. Standacher & H. Shook; The NE orig. BT is only left standing, the old marks still visible, but badly decayed.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Nov. 1969 - C.S. File 54/60-5</p> <p>-----</p> <p>Found - Old, sq. post, partially buried, 1899</p> <ul style="list-style-type: none">Orig. 5" now 13" Maple, alive, N.75°W., 15.8 ft., 3 trees on 1 stump.Orig. 4" now 12" Maple, alive, S.89½°W., 19.8 ft., open & find scribe. <p>continued next page</p>

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. 10" now 22" Maple, alive, N.89°E., 29.0 ft.,
2 trees on 1 stump.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T23S R9W
OFFICE 1969 S 3|S 2
S 10|S 11
18" D.Fir S.25°W., 22.0 ft., mkd: T23S R9W S10 CS BT
12" Hemlock S.88°E. 8.2 ft., mkd: T23S R9W S11 CS BT
8" Hemlock N.31°W., 44.6 ft., mkd: T23S R9W S3 CS BT
No trees suitable to NE.
This corner lies 330 ft. north of top of spur, sloping NW.

Fd. & used on BLM dependent resurvey by Harvey E. Wofford &
Stephen J. Malloy, Cadastral Surveyors, under Group #1005,
surveyed July 1980 - Nov. 1982 - (DCSO records Vol. 43
Page(s) 16858-9)

Fd. Ok by Richard Hintz 6/1984 M 97-6

Carey Weatherly - For: International Paper Co. - 1986 - C.S.
63/55

Found - 1969 Douglas Co. brass cap/iron pipe buried 60"
deep in road side cast.
8" Hemlock stump, face visible, 2 Doug. Co. tags,
N.31°W., 44. 6 ft.
(Other BTs either not found or root wad dug out and
rolled downslope during road construction)
Set - 2" brass cap mkd: "T23S R9W 3|2 1986 LS 1667" on
10|11
36"x1¼" IP 60" above Doug. Co. brass cap. New
BTs- "X" marked on 24" D.Fir bears S.78½°W., 73.1 ft. to
nail in tree, IPCo. tag.
54" D.Fir stump with IPCo. tag bears S.36°E. 46.4 ft

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J.
Flause - April 21, 1987 - C.S. File 62/45-5

Found - 1986 brass cap on 1½" dia., IP protruding 8" above
ground.
1969 DCSO brass cap not looked for, buried 60" per
1986 ren.
10" Maple, now root wad, no blazed or scribing
found, bears N.89°E., 29.4 ft. (Rec. N.89°E.,
29.0 ft. OBT)
No other OBTs found.
5" Maple now a stump that is pushed out of position,
loose & slid down (rec. N.75°W., 15.8 ft. 1899)
continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

No other 1899 BTs found.
8" now 8" dia., 5 ft. high Hemlock stump with a partially healed double blaze & illegible scribing visible bears N.31°W., 44.0 ft. (Rec. N.31°W., 44.6 ft.) 1969
No other BTs per 1969
24" now 29" dia., D.Fir blazed with "X" and a small blaze with line tag below bears S.78½°W., 73.1 ft. 1986
54" dia., 4 ft. high D.Fir stump bears S.36°E., 46.4 ft. 1986
New BTs- 54" dia., 4 ft. high D.Fir stump (per 1986) we set a boat spike stamped "BO 1" through BT tap to top, bears S.36°E., 46.4 ft.
8" Hemlock double blazed & scribed "T23S R9W S3 CS BT" bears N.76½°W., 79.0 ft.
Corner lies on a steep est slope approx. 15. ft. east of the east edge of a dirt logging road.

BLM resurvey by Joseph M Mannix & Edith M Forkner, Cadastral Surveyors Under group No. 2727 surveyed Oct. 2013/April 2014 - (DCSO records Vol. 58 Page(s) 23218-9)

The cor. of secs 2, 3, 10, & 11 perpetuated by the Douglas Co Surveyor's Office, in 1969, further perpetuated by Weatherly, in 1986, and again perpetuated by the Douglas Co Surveyor's Office, in 1987, from original evidence no longer in existence; monumented with an iron post, 1½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.
from which the remains of the bearing trees mkd. by Weatherly
A fir, 36" dia., bears S.78½°W., 74.1 ft., with a healed blaze and an X at breast height.
A fir stump, 54" dia., bears S.34°E., 46.4 ft., to a boat spike added by the Douglas County Surveyor's Office in 1987 in the center of the stump.
and a BT mkd. by the Douglas County Surveyor's Office in 1987
A hemlock, 16" dia., bears N.76¼°W., 78.5 ft., with a healed blaze.
and new bearing trees
A fir, 15" dia., bears N.2½°E., 24.0 ft mkd T23S R9W S2 BT
A fir, 19" dia. bears S.72°E., 11.6 ft mkd T23S R9W S11 BT
From the corner
S.1°52'10"W., 40 ft., graveled road, 8 ft. wide, bears N.20°W. and S.30°E.
Each new bearing tree has a 2½"x1/4" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description. continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.

An aluminum angle iron, 5 ft. long, was driven alongside all corners unless an existing guard post was otherwise noted in the corner description.