

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_


GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 6 Page(s) 2649)

-----  
A point 150 ft. below top of ridge. I set a sandstone 24x16x4", 18" in the ground for cor. of secs. 25, 26, 35, & 36, marked with 1 notch on S & E edges, from which  
A fir, 17" dia., bears N.61°E., 28 lks., mkd: T23S R9E S25 BT.  
A fir, 16" dia., bears S.41°E., 27 lks., mkd: T23S R9E S36 BT.  
A fir, 16" dia., bears S.3°W., 22 lks., mkd: T23S R9E S35 BT.  
A fir, 20" dia., bears N.80°W., 44 lks., mkd: T23S R9E S26 BT.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23298)

-----  
The cor. of secs. 25, 26, 35, & 36, determined at record bearings and distances from the remains of the original BTs  
A fir, 33" dia., bears N.61°E., 18.5 ft., with a healed blaze and an aluminum strip marked PROPERTY LINE DO NOT CUT.  
A fir stump, 33" dia., bears S.41°E., 17.8 ft., with a healed blaze.  
A fir stump, 29" dia., bears S.3°W., 15.9 ft., with a healed blaze and cruiser marks L. (Record and to face, 14.5 ft.)  
A fir, 55" dia., bears N.80°W., 24.7 ft., with a healed blaze. (Record and slope distance, 29.0 ft.)

At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.



There are no new bearing trees available within limits in secs. 35 and 36. Drive an aluminum angle iron alongside the cor.  
From this cor., a point established by person(s) unknown bears N.59°42'03"W., 1.24 ft., and is not used for control in this survey; monumented with an iron pipe, 1" dia., firmly set, projecting 14" above ground.