

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Oscar F. Thiel, Deputy Surveyor under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2663)

-----

Set a Fir post, 3 ft. long, 3" sq. 24" in the ground for ¼ sec. cor. mkd: ¼ S 26 on W face, 25 on E face, from which,  
A Fir, 7" dia., bears N.84½°W., 55 lks., mkd: ¼ S26 BT.  
A Fir, 8" dia., bears S.5°E., 27 lks., mkd: ¼ S25 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - March & April 1967 - C.S. File 54/60-3

-----

Found - Orig. 7" now 28" Fir, alive, N.84½°W., 36.3 ft., shows scar, do not open.  
Orig. 8" now 32" Fir, alive, S.5°E., 17.8 ft., scribe marks visible on previously opened blaze.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T23S R9W OFFICE 1967 ¼ S 26|S 25  
15" Hemlock S.82°E., 53.4 ft., mkd: ¼ S25 CS BT.  
Note - This corner lies 25 ft. South of access road, course E & W.

BLM Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2756, surveyed May 2014 - (DCSO records Vol. 58 Page(s) 23298-9)

-----

The ¼ sec. cor. of secs. 25 & 26, perpetuated by the Douglas County Surveyor's Office in 1967; monumented with an iron post, 1" dia., firmly set, projecting 9" above ground, with a brass cap (properly) mkd.  
from which the original bearing trees  
A fir, 49" dia., bears S.5°E., 17.8 ft., with a healed blaze.  
A fir, 40" dia., bears N.84½°W., 36.3 ft., with a healed blaze.  
and a BT mkd. by the Douglas County Surveyor's Office  
A hemlock, 38" dia., bears S.84°E., 53.4 ft., with a healed blaze.  
Drive an aluminum angle iron alongside the cor.  
From the corner  
N., 45 ft., centerline of Tye Access Road, asphalt surfaced, 10 ft. wide, bears N.85°W. and S.85°E.