

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, under contract # 688, dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2666)

Set Hemlock post, 3 ft long, 4" sq., 24" in the ground, for cor. of secs. 13, 14, 23, & 24, marked T23S S13 on NE, R9W S24 on SE, S23 SW, S14 on NW faces, with notch on E and 3 notches on S edges; from which
A Maple, 18" dia., bears N.12°E., 47 lks., mkd: T23S R9W S13 BT.
A Maple, 10" dia., bears S.7°E., 25 lks., mkd: T23S R9W S24 BT.
A Hemlock, 36" dia., bears S.5°W., 102 lks., mkd: T23S R9W S23 BT.
A Hemlock, 20" dia., bears N.47°W., 32 lks., mkd: T23S R9W S14 BT.
This cor. stands on E side of ridge.

See C.S. File 54/12-3 for 1966 post card.

BLM Dependent resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group #703 surveyed July 1969 - May 1970 - (DCSO records Vol. 35 Page(s) 14552)

Beginning at the cor. of secs. 13, 14, 23, & 24, determined at record bearing & distance from the remaining orig. BTs:
A Maple snag, 30" dia., bears N.12°E., 47 lks., no marks visible.
A Maple, 16" dia., bears S.7°E., 25 lks., no marks visible on opened blaze.
A Hemlock stump, 36" dia., bears S.5°W., 102 lks., no marks visible.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T23 S R9W
S 14 | S 13
S 23 | S 24
1969

from which new BTs:
A Hemlock, 28" dia., bears N.12°E., 105 lks., mkd: T23S R9W S13 BT.
A Hemlock, 13" dia., bears S.50°W., 60 lks., mkd: T23S R9W S23 BT.
A Fir, 23" dia., bears N.24°W., 16 lks., mkd: T23S R9W S14 BT.