

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor under contract # 688, dated June 9, 1898 - (DCSO rec. Vol. 7 Page(s) 2669)

-----  
Set a Hemlock post, 3 ft. long, 3" sq. 24" in the ground for 1/4 sec. cor. mkd: 1/4 S14 on W face and 13 on E face, from which:

- A Maple, 14" dia., bears N.87 1/2°E., 40 lks., mkd: 1/4 S13 BT.
- A Fir, 30" dia., bears N.77°W., 41 lks., mkd: 1/4 S14 BT.

BLM Dependent resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group #703 surveyed July 1969 - May 1970 - (DCSO records Vol. 35 Page(s) 14555)

-----  
The 1/4 sec. cor. of secs. 13 & 14 determined at the record bearing & distance from the orig. BTs:

- A Maple, 23" dia., bears N.87 1/2°E., 40 lks., with healed blaze.
- A Fir, 55" dia., bears N.77°W., 41 lks., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

T23S R9W  
1/4  
S 14 | S 13  
1969

Fd. & used on BLM dependent resurvey by Harvey E. Wofford & Stephen J. Malloy, Cadastral Surveyors, under Group #1005, surveyed July 1980 - Nov. 1982 - (DCSO records Vol. 43 Page(s) 16866)