

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2619)

Marked a Hemlock 5" dia., for the corner to secs. 11, 12, 13, & 14, from which:

- A Fir, 18" dia., bears N.60°E., 100 lks.
- A Maple, 18" dia., bears S.71°E., 60 lks.
- A Fir, 36" dia., bears S.60°W., 27 lks.
- A Fir, 60" dia., bears N.12°W., 30 lks.

BLM Dependent resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group #703 surveyed July 1969 - May 1970 - (DCSO records Vol. 35 Page(s) 14556)

The cor. of secs. 11, 12, 13, & 14, determined at record dist. from the OBTs:

- A roothole, bears N.54°E., 100 lks., with a down Fir alongside, 30" dia., no marks visible. (Rec. N.60°E.)
- A Maple, 36" dia., bears S.77°E., 60 lks., with healed blaze. (Rec. S.71°E.)
- A sawed Fir stump, 40" dia., bears S.54°W., 27 lks., no marks remaining. (Rec. S.60°W.)
- A sawed Fir, stump, 70" dia., bears N.19°W., 30 lks., no marks remaining. (Rec. N.12°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T23S R9W
S 11 | S 12
S 14 | S 13
1969

from which new BTs:

- A Hemlock, 25" dia., bears N.34°E., 101 lks., mkd: T23S R9W S12 BT.
- A Maple, 15" dia., bears S.89°W., 51 lks., mkd: T23S R9W S14 BT.
- A Hemlock, 8" dia., bears N.44°W., 95 lks., mkd: T23S R9W S11 BT.

FD. OK by Mark Smalley, 10/1997 - M124-64

BLM resurvey by Joseph M Mannix & Edith M Forkner, Cadastral Surveyors Under group No. 2727 surveyed Oct. 2013/April 2014 - (DCSO records Vol. 58 Page(s) 23216)

The cor. of secs. 11, 12, 13, & 14; monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd. continued next page

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees
A maple, 53" dia., bears S.77°E., 39.6 ft., no marks visible.
A decayed fir stump, 32" dia., bears S.54°W., 21.2 ft., no marks visible. (Record, 17.8 ft.)
A decayed fir stump, 65" dia., bears N.19°W., 19.8 ft., no marks visible.
and the remains of the BTs mkd. by Jelley & Steward in 1969-70
A hemlock, 41" dia., bears N.34°E., 66.7 ft., with a healed blaze.
A maple, 33" dia., bears S.89°W., 33.7 ft., no marks visible.
A hemlock stump, 9 ft. high, 16" dia., bears N.44°W., 62.7 ft., with a healed blaze.
and a new bearing tree
A fir, 7" dia., bears N.69½°W., 80.1 ft., mkd. X BT.
Alongside the cor. is a steel fence post.
Each new bearing tree has a 2½"x1/4" magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.
Each new corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post, unless otherwise noted in the corner description.
An aluminum angle iron, 5 ft. long, was driven alongside all corners unless an existing guard post was otherwise noted in the corner description.
NAD 1983 (2011)
Latitude: 43°34'48.51"N Longitude: 123°43'38.73" W