TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2620)

Set Fir post, 4" dia., 4 ft. long for the ¼ sec. corner, from which
A Fir, 24" dia., bears N.45°E., 25 lks.
A Fir, 40" dia., bears S.80°W., 50 lks.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & crew - Feb. 1968 - C.S. File 54/60-40

Unrecorded
Found - 1½" IP & brazed cap mkd: ¼ S2|¼ S1 & stumps of possible orig. BTs as follows:
31" Fir stump N.50°E., 19.0 ft., no scribe or scar.
58" Fir stump S.80°W., 36.0 ft., no scribe or scar.
Call on trail fits good.

BLM dependent resurvey by Harvey E. Wofford & Stephen J. Malloy, Cadastral Surveyors, under Group #1005, surveyed July 1980 - Nov. 1982 - (DCSO records Vol. 43 Page(s) 16856-7)

The ¼ sec. cor. of secs. 1 & 2, determined from the remains of an OBT.
A Fir stump, 50" dia., bears S.80°W., 50 lks., with fragmentary scribe marks visible on bark blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: T23S R9W

¼
S 2|S 1
1980

from which
A Fir, 9" dia., bears N.65°E., 30 lks., mkd: ¼ S1 BT.
A Fir, 9" dia., bears S.56¼°W., 28 lks., mkd: ¼ S2 BT.
From this point, a local cor. established by person(s) unknown, bears N.80°E., 0.045 chs. monumented with an iron pipe, firmly set, projecting 12" above ground, with brass cap mkd: ¼ S1 ¼ S2