

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor under contract # 688 dated June 9, 1898 - (DCSO records Vol. 7 Page(s) 2668)

 Set a Cedar post, 3 ft. long, 3" sq. 24" in the ground for ¼ sec. cor. mkd: ¼ S13 on N face and 24 on S face, from which:
 A Fir, 36" dia., bears N.65°W., 26 lks., mkd: ¼ S13 BT.
 A Cedar, 18" dia., bears S.62½°W., 14 lks., mkd: ¼ S24 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & crew - Oct. 1967 - C.S. File 54/60-4

 Found - Orig. 36" now 46" Fir, badly decayed snag, N.65°W., 17.2 ft., no scribe found.
 Orig. 18" now 18" Cedar, turned out, S.62½°W., 9.2 ft., shows "¼ S BT" scribe on burned face.
 Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1967
 T23S R9W
 ¼ $\frac{S\ 13}{S\ 24}$
 15" Hemlock, N.23°W., 13.1 ft., mkd: ¼ S13 CS BT.
 12" Hemlock S.28°W., 17.4 ft., mkd: ¼ S24 CS BT.
 Find also ½" IP with steel sign 7"x11½" stamped "T23S R9W N¼ Sec. 24" set between 13 & 24 established 6-6-66 George C. Barton & Crystal M. Barton, unrecorded 1.0 ft., West of true corner.

BLM Dependent resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group #703 surveyed July 1969 - May 1970 - (DCSO records Vol. 35 Page(s) 14553)

 The ¼ sec. cor. of secs. 13 & 24, perpetuated & recorded by Tracy in 1967, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, w/properly mkd. brass cap. from which the OBTs:
 A Fir, snag 30" dia., bears N.65°E., 26 lks., no marks visible.
 A root hole, bears S.62½°W., 14 lks., with a down Cedar alongside, 20" dia., with scribe marks /4s visible on burned blaze.
 and BTs mkd. by Tracy in 1967
 A Hemlock, 15" dia., bears N.23°W., 19½ lks., with scribe marks ¼ S13 CS BT visible on open blaze.
 A Hemlock, 12" dia., bears S.28°W., 26 lks., with scribe mks. ¼ S24 CS BT visible on open double blaze.

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

And a reference monument established by George C. & Crystal M. Barton in 1966

An IP, 1/2" dia., bears S.53°W., 1 lk. with a metal plate, 1/4x7x12", affixed to top, mkd:

T23S R9W
N1/4 sec. 24
established
6-6-66
George C. Barton
Crystal M. Barton

Fd. & used on BLM dependent resurvey by Harvey E. Wofford & Stephen J. Malloy, Cadastral Surveyors, under Group #1005, surveyed July 1980 - Nov. 1982 - (DCSO records Vol. 43 Page(s) 16862-3)