

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor Secs. 12 & 13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #279, dated March 5, 1878 - (DCSO records Vol. 6 Page(s) 2619)

-----  
Set a Fir post, 4" dia., 40" long for 1/4 sec. cor. from which:  
A Fir, 60" dia., bears N.50°E., 47 lks.  
A Fir, 6" dia., bears S.45°W., 8 lks.

BLM Dependent resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group #703 surveyed July 1969 - May 1970 - (DCSO records Vol. 35 Page(s) 14557-8)

-----  
The 1/4 sec. cor. of secs. 12 & 13 determined at the record bearing & distance from the remaining orig. BT:

A Fir, 60" dia., bears N.50°E., 47 lks., no marks visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

T23S R9W  
          S 12  
1/4        S 13  
          1969

from which

A Hemlock, 20" dia., bears N.51°W., 58 1/2 lks., mkd: 1/4 S12  
BT.

A Hemlock, 20" dia., bears S.78°E., 45 1/2 lks., mkd: 1/4 S13  
BT.

Fd. & used on BLM dependent resurvey by Harvey E. Wofford & Stephen J. Malloy, Cadastral Surveyors, under Group #1005, surveyed July 1980 - Nov. 1982 - (DCSO records Vol. 43 Page(s) 16864)

Clyde Mulkins, L.S. #2008 - For: IP Timberlands Operating Co. LTD. - 4/1994 - M 118-71

-----  
Found - A 1969 BLM Brass Cap, from which:  
26" Hemlock w/ healed face bears N.51°W 36.9' (rec. 58 1/2 lks)  
57" DF with healed face bears N.50°E., 30.5' (rec. 47 lks.).  
26" Hemlock w/visible scribes bears S.75°E., 30.5' (rec. S.78°E., 45 1/2 lks.).  
New BT- 13" Hemlock, bears N.69°E., 21.4', scribed "1/4 S12  
BT"

Fd. Ok by Mark Smalley, 10/1997 - M 124-64