

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 700359

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only, T23-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2546)

-----  
Set a stone 18x6x5 ins., 14" in the ground for ¼ sec. cor. marked ¼ on W. face, from which  
A Fir 24" dia., bears N.2°E., 13 lks. dist. mkd. ¼ S BT.  
A Fir 30" dia., bears N.60°W., 33 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Feb. 1967 - C.S. File 54/12-23A

-----  
Looked for, not found.

BLM resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group # 703, surveyed July 1969/May 1970 (DCSO records Vol. 35 Page(s) 14542-43)

-----  
The ¼ sec. cor. of sec. 19 only, determined at record bearing and distance from the original bearing trees:  
A root hole bears n.2°E., 13 lks. dist., with a down Fir alongside 30" dia., no marks visible.  
A root hole bears N.60°W., 33 lks. dist., with a down Fir alongside, 38" dia., with scribe marks BT visible on opened double blaze.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T 23 S  
R 8 W  
¼ S 19  
1969

from which new bearing trees  
A Hemlock 12" dia., bears N.77°E., 57 lks. dist. mkd. ¼ S19 BT.  
A Hemlock 8" dia., bears N.41 3/4°E., 57 lks. dist. mkd. X BT.

Fd. and used in BLM Resurvey by Harvey E. Wofford and Stephen J. Malloy, Cadastral Surveyors, under Group #1074, Surveyed July 1980/Nov. 1982 - (DCSO records Vol. 43 Page(s) 16846)