

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION C C for Secs. 13 & 24 only, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #688 dated June 9, 1898 (DCSO records Vol. 7 Page(s) 2667)

(20.10 chs. S. of cor. of secs. 18 & 19)
At point of intersection, I set a Cedar post 3 ft. long, 4" sq., 24' in the ground for closing cor. of secs. 13 and 24, marked C C T23S R9W on W.; S13 on N.; S24 on S.; faces, with 3 notches on N. and S. faces, from which
A Fir 16" dia., bears N.27°W., 27 lks. dist. mkd. T23S R9W S13 BT.
A Maple 12" dia., bears S.55°W., 17 lks. dist. mkd. T23S R9W S24 BT.

BLM resurvey by James E. Jelley and Rolla R. Steward, Cadastral Surveyors under Group # 703, surveyed July 1969/May 1970 (DCSO records Vol. 35 Page(s) 14543)

Point for the closing cor. of secs. 13 and 24, T23S R9W at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 23 S
R 9 W
CC S 13 S 19
S 24
1969

from which
A Cedar 35" dia., bears N.31½°W., 37 lks. dist. mkd. T23S R9W S13 CC BT.
A Fir 35" dia., bears S.89°W., 59 lks. dist. mkd. T23S R9W S24 CC BT.

Fd. and used in BLM Resurvey by Harvey E. Wofford and Stephen J. Malloy, Cadastral Surveyors, under Group #1074, Surveyed July 1980/Nov. 1982 - (DCSO records Vol. 43 Page(s) 16846)