

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 700459

PRIMARY CORNER DESCRIPTION W. 1/4 cor. Sec. 18 only, T23-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2547)

-----  
Set a post 3 ft. long, and 3" sq., 2 ft. in ground for ¼ sec. cor. marked ¼ S on West face, from which,  
A Fir 40" dia., bears S.5°E., 143 lks. dist. mkd. ¼ S BT  
A burnt Fir 12" dia., bears N.10°W., 14 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
Jan. 1967 - C.S. File 54/12-11

-----  
Found - Orig. 40" D.Fir, now snag S.5°E., 94.4 ft. scribe "4S" in the wood, there were two good faces plus ring count.

No trace of other BT.

Set Brass cap at cor. mkd: County Surveyors Office

R		T 23 S	R
9 ¼		S 18	8
W			W

1967

New BTs- 30" W.Fir S.47°E., 14.5 ft. mkd. ¼ S18 CS BT.

11' W.Fir N.61°E., 36.8 ft. mkd. ¼ S18 CS BT.

This corner lies on top of ridge, course West.

Fd. and used in BLM resurvey by James E. Jolley and Rolla R. Steward, Cadastral Surveyors under Group # 703, surveyed July 1969/May 1970 (DCSO records Vol. 35 Page(s) 14545)