

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, T23-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2549)

-----

Set a post 4 ft. long, 4" sq., 2 ft. in the ground mkd. S6 on N. side; T23S R8W on E. side; and S7 on S. side, with 1 notch on N. and 5 notches on S. faces, from which

A Fir 24" dia, bears N.70°E., 64 lks. dist. mkd. T23S R8W S6 BT.

A Hemlock 20" dia., bears s.79°E., 85 lks. dist. mkd. T23S R8W S7 BT.

A Fir 30" dia., bears N.2°W., 100 lks. dist. mkd. T23S R8W S6 & 7 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb. 1967 - C.S. File 54/12-23A

-----

Looked for, not found

BLM survey by Harvey E. Wofford, Cadastral Surveyor, under Group #1005, surveyed July/Dec. 1980 - (DCSO records Vol. 43 Page(s) 16834)

-----

(96.43 chs.)

True point for the cor. of secs. 6 & 7 only.

Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd:

T 23 S      T 23 S  
R 9 W      S 6  
            S 7  
S 12      R 8 W  
            1980

from which

A Hemlock 18" dia., beas N.37°E., 71 lks. dist. mkd. T23S R8W S6 BT.

A Hemlock 17" dia., bears S.72½°E., 14½ lks. dist. mkd. T23S R8W S7 BT.

(96.55 chs. N.89°17'W)

The original cor. of secs. 6 and 7 only, monumented with a steel fence post, firmly set, projecting 26" above ground, from which the remains of the original bearing trees:

A Fir stump 33" dia., bears N.70°E., 66½ lks. dist. with healed blaze. (Rec. and to face, 64 lks.)

A Fir 49" dia., bears N.2°W., 100 lks. dist. with healed blaze.

(Cont. next page)

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 700566

PRIMARY CORNER DESCRIPTION Corner Secs. 6 & 7 only T23-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Mark Smalley - For: Riverbend Resources - Oct. 1997 -  
M 124-64

-----

Found - 1980 Cadastral Brass Cap on Iron pipe.  
20" Hemlock, S.72½°E., 9.6' down.  
19" Hemlock, N.37°E., 46.7' (46.9' - 1980) healed.  
New BTs- 12" D.Fir, S.10°W., 23.3', scribed "S12 BT"  
16" Hemlock, S.26°E., 25.1', scribed "S7 BT"  
Note- Steel post marking orig. corner bears, West. 8.6',  
(9.6' -1980)  
BTs - 30" D.Fir stump, N.70°E., 42.2', OBT.  
52" D.Fir, N.2°W., 66.0', OBT.