

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 700627

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only, T23-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2550)

Set a post 3" sq., 3 ft. long, 2 ft. in the ground for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 20" dia., bears S.10°E., 27 lks. dist., mkd. ¼ S BT
A Hemlock 8" dia., bears N.45°W., 27 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Feb/March 1967 - C.S. File 54/12

Found - Orig. 8" now 12" Hemlock, very badly decayed stump, N.45°W., 17.8 ft. Open and find reverse scribe in decayed log on ground.
Orig. 20" now 34" Fir, alive, S.1°E., 17.8 ft. (Rec. S.10°E.) Shows scar. Do not open.
Set Brass cap at cor. mkd: County Surveyors Office
T 23 S R 8 W
¼ S 6
1967
New BTs- 9" Hemlock N.74½°E., 10.8 ft. mkd. ¼ S6 CS BT.
14" Hemlock N.47°E., 19.0 ft. mkd. ¼ S6 CS BT.
Also, unrecorded 1½" I.Pipe bears N.71°W., 3.9 ft.
Corner lies on top of small spur ridge, course NW.

BLM Resurvey by Harvey E. Wofford and Stephen J. Malloy, Cadastral Surveyors, under Group #1074, Surveyed July 1980/Nov. 1982 - (DCSO records Vol. 43 Page(s) 16850-51)

True point for the ¼ sec.cor. of sec. 6 only, T23S R8W.
Set an alum. post 28" long, 2p" dia., 24" in the ground, with alum. cap mkd. T 23 S
R 9 W R 8 W
1/4 S 6
1980
from which
A Hemlock 8" dia., bears N.9½°E., 17 lks. dist. mkd. X BT.
A Hemlock 9" dia., bears S.48½°E., 40 lks. dist. mkd. ¼ S6 BT.

From this point, the original ¼ sec. cor. of sec. 6 only, bears N.89°23'W., 0.05 chs. dist., perpetuated and recorded by Tracy in 1967, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground with brass cap mkd. in (Cont. Next Page)

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 700627

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only, T23-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

1967, from which the remains of the original bearing trees:
A Fir 35" dia., bears S.1°E., 27 lks. dist., with healed blaze.

A decayed Hemlock stump, size indeterminate, bears N.45°W., 27 lks. dist., with old axe marks visible on bark.

and bearing trees mkd. by Tracy:

A Hemlock 19" dia., bears N.47°E., 29 lks. dist., with healed blaze.

A Hemlock 12" dia., bears N.74½°E., 16½ lks. dist., with healed blaze.

From this point, a point established by person(s) unknown, bears N.74°00'W, 0.06 chs. dist., monumented with an iron pipe 1½" dia., firmly set, projecting 12" above ground.

The cor. is located on a spur, slopes N.25°W.