

PRIMARY CORNER DESCRIPTION NE Cor. Section 1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 279 survey dated March 5, 1878 (DCSO records Vol. 4 Page(s) 1651-52)

Set post 5" dia., 4 ft. long, 20" in ground, for the cor. to T22 and 23, R8 and 9 W., from which
A Fir 36" dia., bears N.20°E., 24 lks. dist.
A Chinquapin 12" dia., bears S.70°E., 40 lks. dist.
A Fir 20" dia., bears S.50°W., 24 lks. dist.
A Fir 24" dia., bears N.88°W., 29 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - March 1963 - C.S. File 52/14-54

Found - 1½" galv. Iron pipe at corner.
Old, uprooted Fir, now 32", N.88°W., 19.1 ft., traces of old scribing visible on previously opened face. "S" only legible.
Old, uprooted Fir now 30", S.50°W., 15.8 ft., lying face down.
40" Fir stump, N.20°E., 15.8 ft., bark flaking badly, no marks visible.
27" hollow Chinquapin snag, S.70°E., 26.4 ft., both upper and lower blaze visible on bark, but entire center rotted away.
Did Not Set Brass Cap. Cor. lies on top of ridge.
New BTs -13" W.Fir S.41°E., 31.4 ft. mkd. T22S R9W S36 CS BT.
12" W.Fir S.49°W., 58.3 ft. mkd. T23S R9W S1 CS BT.

BLM survey by Harvey E. Wofford and Stephen J. Malloy, Cadastral Surveyors, under Group #1074, surveyed July 1980/Nov. 1982 - (DCSO records Vol. 43 Page(s) 16852-53)

The NE. cor. of T23S R9W, perpetuated and recorded by Godfrey in 1963, monumented with an iron pipe 1½" dia., firmly set, projecting 15" above ground, from which the remains of the original bearing trees:
A Fir stump 40" dia., bears N.20°E., 24 lks. dist., no marks visible.
A decaying Chinquapin snag, size indeterminate, bears S.70°E., 40 lks. dist. no marks visible.
A roothole bears S.50°W., 24 lks. dist. alongside of which is a downed, decayed Fir, 30" dia., no marks visible.
A roothole bears N.88°W., 29 lks. dist. alongside of which is a downed Fir 32" dia., with illegible scribe marks visible on opened blaze.

(Cont. Next Page)

TOWNSHIP 23 RANGE 09 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Cor. Section 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a bearing tree mkd. by Godfrey:

A W.Fir 20" dia., bears S.41°E., 47½ lks. dist. with a healed blaze.

At the corner point

Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with alum. cap mkd:

T 22 S	R 9 W
T 23 S	S 36
R 9 W	
S 1	
1980	

from which a new bearing tree

A Fir 10" dia., bears S.88 3/4°W., 41 lks. dist. mkd. T23S R9W S1 BT.

Deposit the iron pipe alongside the iron post.

The cor. is located on top of a spur ridge, bears N.15°W., and S.15°E.