

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Levi C. Walker under contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2724)

Set a Hemlock post, 3' long, 4" sq., 24" in the ground, for the ¼ sec. cor. mkd: ¼ S33 on W & 34 on E face, from which
A Hemlock, 20" dia., bears S.69°E., 39 lks., mkd: ¼ S34 BT
A Fir, 30" dia., bears N.74°W., 51 lks., mkd: ¼ S33 BT.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/1933 - FB 119 Pg. 3 & C.S. File 49/80 (Filed 4/24/1958)

Replace post, 3"x3" Hemlock post 24" above ground mkd: ¼ S33 on E face & 34 on W.
OBTs standing:
24" Hemlock S.69°E., 26 ft.
36" Fir N.74°W., 34 ft.

Arnold G. Gibson, Oregon St. Board of Forestry - 5/17/1960 - C.S. File 42/422-5

Found - Orig. post, now missing - fd. hole where rotted out) from which a:
24" Hemlock bears S.69°E., 39 lks., now 32" face overgrown.
36" Fir bears N.74°W., 51 lks., now 42" scribes BT visible.
Set - 1½"x36" gal. IP with 3" bronze cap mkd as usual
Orig. 24" Hemlock bears S.69°E., 25.7 ft., scribed RS359 (near bottom)
Orig. 36" Fir bears N.74°W., 33.7 ft., scribed BT (near bottom)
Oregon St. Bd. of Forestry metal location poster on Orig. 24" Hemlock BT, also a Douglas Co. Forest App. tag on BT
4"x4"x6' white painted Cedar post N.45°E., 1,5 ft. from pipe.

Please note that this corner is on the Douglas Co. & Coos Co. line and Coos Co. Surveyor's Office may have more information concerning this corner.