

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION cor Secs 27, 28, 33, & 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Levi C. Walker under contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2723)  
-----  
Set a Fir post, 3' long, 4" sq., 24" in the ground, for the cor. of secs. 27, 28, 33, & 34 mkd: T23S S27 on NE., R10W S33 on SE., S33 on SW, and S28 on NW face, with 1 notch on S & 3 notches on E edge, from which  
A Fir, 20" dia., bears N.26°E., 25 lks., mkd: T23S R10W S27 BT.  
A Fir, 18" dia., bears S.52°E., 32 lks., mkd: T23S R10W S34 BT.  
A Fir, 14" dia., bears S.57°W., 84 lks., mkd: T23S R10W S33 BT.  
A Fir, 8" dia., bears N.79°W., 124 lks., mkd: T23S R10W S28 BT.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/1933 - FB 119 Pg. 6 & C.S. File 49/80-1 pg 7 (Filed 4/24/1958)  
-----  
Fir post 3" sq. 3 ft. long.  
24" Fir N.26°E., 16.5 ft.  
18" Fir S.52°E., 21 ft.  
20" Fir S.57°W., 55 ft.  
65 ft. North to Loon Lake Rd.

Arnold G. Gibson, Oregon St. Board of Forestry - Elbert Driver - Witnesses: R. Banks, D. Timmons & D. McConnell - Jan. 1958 - C.S. File 42/422-1  
-----  
Found - Orig. post, now missing from which a:  
20" Fir bears N.26°E., 25 lks., now 27" uproot, face grown over.  
18" Fir bears S.52°E., 32 lks., now 20" uproot, face grown over.  
14" Fir bears S.57°W., 84 lks., now 24" orig. axe work & portion of scribe visible.  
8" Fir, bears N.79°W., 124 lks., now missing  
Set- 1½"x36" gal. IP with 3" bronze cap mkd: OREGON STATE BOARD OF FORESTRY T23S R10W S27 S28 S33 S34 1958 RS359, 33" in ground, and from which a:  
27" Fir N.26°E. 45.9' scribed T23S R10W S27 BT RS359  
15" Fir N.43°W., 37.8 ft., scribed T23S R10W S28 BT.  
22" Fir S.42°E., 23.4 ft., scribed T23S R10W S34 BT.  
24" Fir S.66°W., 74.1 ft. scribed T23S R10W S33 BT.  
Ore. St. Bd. of Forestry metal location poster on 22" Fir BT

continued next page

1

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 7/23/1992 - C.S. File 64/31-1

-----  
Found - 3" dia., bronze cap (OSBF) on 1½" ID galv. IP,  
firmly set, and protruding 6" from ground.  
No evidence of orig. BTS found, logging & road work  
in area has obliterated remains of windfalls &  
old stumps. 1958  
A 27" Fir now a 3 ft. tall 48" dia., D.Fir stump  
with a fully healed single blaze bears N.26°E.,  
46.7 ft., rec. N.26°E., 45.9 ft., this is a  
reasonable measurement. 1933  
A 15" Fir now an uprooted 7 ft. tall 22" DBH Fir  
stump with a fully healed single blaze, the root  
hole of which agrees well with the record bearing  
& distance N.43°W., 37.8 ft. 1958  
22" Fir now a 2½ ft. tall 28" dia., D.Fir stump with  
the scribing "S R10W S" visible in the remains of  
a partially opened single blaze bears S.39°E.,  
24.4 ft. dist., rec. S.42°E., the dist. is a  
reasonable face measurement. 1958  
No evidence of SW BT is found, measurement falls in  
a road.  
An unrecorded reference is found, a rotted 2 ft.  
tall 6" dia. Chinquapin stump with a Weyerhaeuser  
location tag bears S.28°W., 12.8 ft. dist.,  
agrees w/Weyerhaeuser tag.  
New BTs- A 4" DBH D.Fir scribed "X BT" on a double blaze  
bears S.17¼°E., 35.3 ft.  
A 5" DBH Chinquapin scribed "X BT" on a double blaze  
bears S.26°W., 13.2 ft.  
Monument is in a recent clearcut North of a older clearcut &  
between roadways as shown in sketch in CS File. Monument is  
approx. 250 ft. ENE from large D.Fir snag wildlife tree.

James M. McIntosh - For: Oregon Dept. of Forestry - 7/1999 -  
M 133-14

-----  
Found - Oregon ST. BD. of Forestry 1½"x36" IP w/3" bronze  
cap in place. 1958  
27" Fir N.26°E., 45.9 ft. (now 51"x3' high stump in  
place, face closed, WEYCO Tag) 1958  
15" Fir, N.43°W., 37.8 ft., (now 21"x7' long uproot,  
face closed, WEYCO tag & yellow metal location  
poster) 1958  
22" Fir S.42°E., 23.4 ft. yellow metal location  
poster (now 26"x2½' high rotten stump in place,  
face exposed & rotten, WEYCO tag) BT tag. 1958  
continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION cor Secs 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

24" Fir S.66°W., 74.1 ft., now missing, falls in old road. 1958  
6"x2' high Chinquapin stump (WEYCO) S.28°W., 12.8 ft. (now very rotted stump in place)  
4" Fir, S.17¼°E., 35.3 ft., now 8" in place face closed, BT tag. DCSO 1992  
5" Chinquapin S.26°W., 13.2 ft., now 7" in place, scribes visible, BT tag. DCSO 1992  
New B0s- Orange Carsonite marker CBM-250 Labeled Witness post bears S.34°W., 2.85 ft. to base.  
Orange Carsonite marker CBM-250 Labeled Witness post bears N.50°W., 3.85 ft. to base.  
Orange Carsonite marker CBM-250 Labeled Witness post bears N.47°E., 3.35 ft. to base.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/19/2019 (Filed 11/3/2022) - C.S. File 67/54-32  
-----  
Found - A 3" dia., bronze cap on 1½" I.D. iron pipe. Cap is marked as described, proj. 5" above ground. 1958 OSBF.  
A 48" dia., 3 ft. tall D.Fir stump (as described); bears N.26°E., 45.9 ft. (as per rec) 1958 OSBF  
A roughly 14" dia., x 2½" tall Fir stump with scribed face rotted away; bears S.39°E., 24.4 ft. (rec S.42°E., 23.4 ft good to orig face) 1958 OSBF  
A mostly rotted away uprooted Fir stump, the roothole of which bears N.43°W., 37.8 ft. (as per record) 1958 OSBF  
A 19" dia. D.Fir with a fully healed high-low blaze; bears S.17¼°E., 35.3 ft. (as per rec) DCSO 1992  
An 11" chinquapin with a fully healed high-low blaze bears S.26°W., 13.4 ft. (rec. 13.2 ft) DCSO 1992  
From the 1999 ODF survey 3 bearing objects are fd. All are orange carsonite markers as described and at record B & D.  
New - A 10" dia., Hemlock, scribed "T23SR10W S27" "CSBT" on a double blaze; bears N.35°E., 9.7 ft.  
A 10" dia. D.Fir, scribed "T23SR10WS28CS" "BT" on a double blaze; bears N.35½°W., 25.4 ft.  
Note - Compass decl. 15°E.

Stephen Stys - Crew: Brandon Campbell, John Rondeau & Daniel Tiemissen - 1/2023 - C.S. File 65/111-37  
-----  
Found - A 1½" galvanized pipe w/ 3" bronze cap (properly mkd) set per (CS file 42/422).  
Continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION cor Secs 27, 28, 33, & 34

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A 43" Fir stump w/a healed face & tag bears N.26°E., 46.1' (Per M133-14).  
A 12" Hemlock w/visible scribe in face and tag bears N.35°E., 9.7' (Per CS File 67/54-32).  
A 14" rotten Fir stump w/tag but no visible marks bears S.39°E., 24.4' (PER CS FILE 64/031-1).  
A 20" D.Fir w/a healed face & tag bears S.17°15'E., 35.3' (Per CS File 64/031-1).  
AN 11" Chinquapin w/healed face & tag bears S.26°W., 13.4' (Per CS File 67/54-32)  
A root hole next to an uprooted rotten stump w/ tag bears N.43°W., 37.8' (Per M133-14).  
AN 11" Fir w/visible scribe in face and tag bears N.35°30'W., 25.4' (Per CS File 67/54-32).  
B0s - A Carsonite post bears N.47°E., 3.35' (Per M133-14)  
A Carsonite post bears S.34°W., 2.85' (Per M133-14)  
A Carsonite post bears N.50°W., 3.85' (Per M133-14)  
Note - Lat. & Long. Per GARMIN ETREX HANDHELD GPS  
N:43°31'50.1" W:123°52'32.7"  
Lat. and Long. are from a GARMIN ETREX hand held GPS and does not produce survey coordinates.  
Compass declination 14.5°EAST

Please note that this corner is on the Douglas Co. & Coos Co. line and Coos Co. Surveyor's Office may have more information concerning this corner.