

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Levi C. Walker under contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2741)  
-----  
Intersect E end of a stone, 24x20x20 ins. above ground. Cut a + at exact place for 1/4 sec. cor., marked 1/4 on N face, (the W face being inaccessible); from which  
A Fir, 12" dia., bears N.15°E., 15 lks., mkd: 1/4 S10 BT.  
A Fir, 6" dia., bears N.4°W., 24 lks., mkd: 1/4 S9 BT.

Arnold G. Gibson, Oregon St. Board of Forestry - June 19, 1962 - C.S. File 42/331-8  
-----  
Found - Orig. stone 24"x20"x20", crumbled stone in place, no marks visible, from which a:  
12" Fir bears N.15°E., 15 lks., now 37" face closed.  
6" fir bears N.4°W., 24 lks., now 13" snag, scribes S9 exposed.  
Set - 1 1/2"x36" galv. IP w/3" bronze cap mkd: OREGON STATE BOARD OF FORESTRY 1/4 S9 S10 1962 RS 359, 32" in ground, and from which a:  
24" Fir N.57 1/2°W., 50.8 ft., scribed 1/4 S9 BT RS 359.  
Oregon St. Forestry Dept. metal location poster on orig. 12" BT.  
4"x4"x72" white painted Cedar post 2 ft. NW of corner pipe.

Please note that this corner is on the Douglas Co. & Coos Co. line and Coos Co. Surveyor's Office may have more information concerning this corner.