

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Levi C. Walker under contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2741-2)

Set a basalt stone 24x6x6 ins., 18" in the ground, for cor. of secs. 3, 4, 9, & 10, marked with 5 notches on S & 3 notches on E edge, from which

A Fir, 10" dia., bears N.76°E., 124 lks., mkd: T23S R10W S3 BT.

A Fir, 8" dia., bears S.86°E., 84 lks., mkd: T23S R10W S10 BT.

A Fir, 8" dia., bears S.73°W., 81 lks., mkd: T23S R10W S9 BT.

A fir, 12" dia., bears N.41°W., 150 lks., mkd: T23S R10W S4 BT.

Per a 1967 map received from the Coos County Surveyor's Office there has been a corner renewal recorded at the Coos County Surveyor's Office that the Douglas County Surveyor's does not have. Please note that this corner is on the Douglas Co. & Coos Co. line and Coos Co. Surveyor's Office may have more information concerning this corner.