

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 4 Page(s) 1742)

Marked a Hemlock 6" dia., for the cor. to secs. 3 & 4, on N. bdy., from which
A Hemlock 5" dia., bears S.45°E., 7 lks.
A Hemlock 7" dia., bears S.60°W., 25 lks.

GL0 survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1759)

A Hemlock 10" dia., marked for cor. to secs. 3 & 4 with S3 on E.; T23S R10W on S.; S4 on W. with 3 notches on E. and W. faces, from which
A Hemlock 5" dia., bears S.45°E., 70 lks. dist. mkd. T23S R10W S3 BT.
A Hemlock 7" dia., bears S.60°W., 24 lks. dist. mkd. T23S R10W S4 BT.

GL0 survey by Levi C. Walker, Deputy Surveyor, under Contract #763, dated June 20, 1905 - (DCSO records Vol. 5 Page(s) 1847 AND Vol. 7 Page 2744))

(Page 1847)
Intersect a Hemlock tree 12" dia., originally marked for the cor. of secs. 3 and 4, T23S R10W. All marks are obliterated. (Page 2744)
Set Fir post 3 ft. long, 4" sq., 24" in the ground for CC of secs. 3 and 4, marked CC T23S R10W on S.; S3 on E.; and S4 on W. face, with 3 grooves on E. and W. faces, from which
A Hemlock 12" dia., bears S.59°E., 40 lks. dist. mkd. T23S R10W S3 BT.
A Fir 7" dia., bears S.81°W., 22 lks. dist. mkd. T23S R10W S4 BT.
I make diligent search but find no trace of old cor. of secs. 3 and 4, described as a Hemlock post, 6" sq., with bearing trees.

Survey by Arnold Gibson, D.L. McConnell, Transitman - For: Oregon State Board of Forestry - March 1962 - C.S. 42/331-7

Orig. Fir post, now missing, from which a:
12" Hemlock bears S.59°E., 40 lks.; now down, scribes T2S R10 S3 visible.
(Cont. Next Page)

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for secs. 3 & 4 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

7" Fir bears S.81°W., 22 lks.; rotten root crown in place.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd: "Ore. St.
Bd. of Forestry S34 T22S R10W S4 S3 CC T23S R10W 1962 RS
359", 30" in ground, from which a:
24" Fir bears S.80½°E., 23.1 ft. scribed CC T23S R10W S3
BT RS 359.
20" Hemlock bears S.32°W., 32.5 ft. scribed CC T23S R10W
S4 BT.
OSBF metal location poster on 24" Fir BT.
Set 4"x4"x72" painted white cedar post 1.0 ft. SW. of corner
pipe. Original line blaze on 26" Hemlock, South 16.7 ft.

Please note that this corner is on the Douglas Co. & Coos Co.
line and Coos Co. Surveyor's Office may have more information
concerning this corner.