

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 402100

PRIMARY CORNER DESCRIPTION Angle Point on So. Bdy. Sec. 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 7 Page(s) 2701)

Set a Maple post 5 ft. long, 5" dia., 20" in ground for the cor. between secs. 3, 4, 33 and 34, from which
A Fir 24" dia., bears N.78°E., 10 lks. dist.
A Fir 30" dia., bears S.65°E., 7 lks. dist.
A Fir 16" dia., bears S.74°W., 20 lks. dist.
A Fir 24" dia., bears N.15°W., 28 lks. dist.

Arnold G. Gibson - For; Oregon Dept. of Forestry - June 10, 1960 - C.S. File 42/422-6

Found Maple post, now missing, from which a:
24" Fir bears N.78°E., 10 lks.; now 34" scribes S34 T23S R10W visible.
30" Fir bears S.65°E., 7 lks.; now 36", scribes S3 visible.
16" Fir bears S.74°W., 20 lks.; now rotted 2 ft. high stub
24" Fir bears N.15°W., 28 lks.; now 30" rotted stub, axe work remaining.

Surveys in 1896 and 1905 reported destroying corner and defacing overgrowth was not chopped out then.

Restored as an angle point

Set 1½" x 36" galv. Iron pipe with 3" bronze cap mkd. "Ore. St. Bd. of Forestry T23S R10W AP S34 S3 T24S 1960 RS 359", 32" in ground, and from which a:

30" Fir bears S.85°W., 26.2 ft. scribed RS 359.

Oregon State Board of Forestry metal location poster on orig. 30" Fir BT.

Set 4x4x72" White painted Cedar post 1.5 ft. NE of pipe.

Tony Hostetter - For: Weyerhaeuser Co. - May 27, 2015 - C.S. File 65/89-48

Found - 1960 Oregon St Board of Forestry brass cap as described by Gibson, C.S. File 42/422

34" fir stump, OBT WEYCO tag & "W" nail, bears N.78°E., 6.6 ft. to center.

30" fir stump, OBT WEYCO tag & "W" nail, bears S.65°E., 4.6 ft. to center.

32" Fir stump, Gibson BT, scribing visible, tag & "W" nail, bears S.85°W., 26.2 ft. to center.

New BTs- 11" Fir, BT tag, bears N.12°E., 3.0 ft. to 6" spike, placed below tag.

14" Fir, BT tag, bears S.74°W., 8.1 ft. to 6" spike, placed below tag.