

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Levi C. Walker under contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2723)  
-----  
Set a Fir post, 3 ft. long, 3" sq., 24" in the ground, for ¼ secs. cor. mkd: ¼ S27 on N and 34 on S face; from which  
    A Fir, 13" dia., bears S.53°E., 14 lks., mkd: ¼ S34 BT.  
    A Fir, 13" dia., bears N.59°W., 19 lks., mkd: ¼ S27 BT.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/1933 - FB 119 Pg. 7 & C.S. File 49/80-1 pg 7 (Filed 4/24/1958)  
-----  
Old corner post & orig. BTs located:  
    18" Fir N.59°W., 12.5 ft. OBT  
    16" Fir S.53°E., 16 ft - OBT  
Replace post with 3"x3' Hemlock

Arnold G. Gibson, Oregon St. Board of Forestry - 11/22/1961 - C.S. File 42/422-8  
-----  
Found - Orig. fir post, now missing, from which a:  
    13" Fir bears S.53°E., 14 lks., now 17", exposed scribes S34.  
    13" Fir bears N.59°W., 19 lks., now 25", face grown over.  
Set - 1½"x36" galv. IP with 3" bronze cap mkd: "Ore. St. Bd. of Forestry ¼ S27 S34 1961 RS359", 32" in ground, in mound of stone, & from which a:  
    21" Fir bears N.16°W., 51.1 ft., scribed RS359.  
    Ore. St. Bd. of Forestry metal location poster on orig. 13" Fir BT NW.  
    4"x4"x72" white painted cedar post 1.5' NE of pipe.

James M. McIntosh - For: Oregon Dept. of Forestry - 7/1999 - M 133-14  
-----  
Found - Oregon ST. Dept. of Forestry 1½"x36" Alum. pipe with 3 3/4" alum. cap w/magnetic insert 34" in ground.  
    18" Fir N.1°E., 69.7 ft. to alum. nail in BT face scribed ¼ S27 BT. BT tag.  
    WP N.52°E., 3.5 ft. to base.  
    7" Hemlock S.2°E., 4.7 ft. to aluminum nail in BT face scribed ¼ S34 BT. BT tag.  
    WP S.38°W., 1.8 ft. to base.  
    1" iron pipe S.73°E., 0.45 ft.  
Note - Information below is taken from Weyerhaeuser records dated 1978  
continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

55" Fir stump N.24°W., 121.3 ft.  
20" Fir stump N.77½°E., 65.1 ft.  
10" Maple S.82½°W., 62.2 ft.  
Bearing & distances were measured from the spikes in the 2 remaining Fir stumps to the 1" IP. Those measurements are shown below.  
55"x2' high rotted stump N.19°W., 121.9 ft.  
14"x1' high rotted stump N.77°E., 68.0 ft.

Stephen Stys - Crew: Brandon Campbell, John Rondeau & Daniel Tiemissen - 1/2023 - C.S. File 65/111-38  
-----  
Found - A 1½" aluminum pipe w/3¾" aluminum cap (properly mkd except for date - should be 2103 not 2301) set per M133-14  
A 27" Fir w/a healed face and tag bears N.1°E., 69.7' (Per M113-14).  
A Rotten stump and tag bears N.77°30'E., 65.1' (Per M113-14).  
An 11" Hemlock w/a healed face and tag bears S.2°E., 4.7' (Per M113-14).  
A 55" Fir stump bears N.24°W., 121.3' (Per M113-14)  
A 1" iron pipe bears S.73°E., 0.45' (Per M113-14)  
NEW - A 14" Alder, bark scribed "S¼ S27 BT" with X-Chop and tag bears N.59°E., 24.7' to a spike at side center.  
A 14" Hemlock, faced and scribed N¼ S34 BT with X-Chop and tag bears S.74°W., 21.2' to a spike at side center.  
Note - Lat. and Long. Per GARMIN ETREX handheld GPS  
N: 43°31'49.9" W: 123°51'56.9"  
Lat. & Long. are from a GARMIN ETREX hand held GPS & does not produce survey-grade coordinates