

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Levi C. Walker under contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2742)

Cut a + on face of sandstone bluff at exact point of ¼ sec. cor., from which

A fir, 6" dia., bears S.21°E., 14 lks., mkd: ¼ S10 BT.

A fir, 6" dia., bears N.73°W., 28 lks., mkd: ¼ S3 BT.

James M. McIntosh, Oregon Dept. of Forestry - Ralph C. Hall, witness - May 19, 2012 - C.S. File 65/76-57

Found - X on face of sandstone bluff (in place) from which
6" Fir S.21°E., 14 lks. - missing.
6" Fir N.73°W., 28 lks. - now 26"x1 ft. high rotted stump in place, exposed bottom of face, no marks visible.

RE-WITNESSED from original X on face of sandstone bluff:

7" Fir S.89°E., 4.4 ft. to aluminum nail in BT face scribed (¼ S10 BT) BT tag.

8" Fir S.10°E., 15.2 ft. to aluminum nail in BT face scribed (¼ S10 BT) BT tag.

6" Fir N.39°W., 16.2 ft. to aluminum nail in BT face scribed (¼ S3 BT) BT tag.

Carsonite Witness Post N.70°W., 16.6 ft. to base.

Magnetic variation set at 19° East.