

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 34 & 35 only, T22-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 4 Page(s) 1742)

Marked a Fir 36" dia., at foot of perpendicular bluff 30 ft. high, for the cor. to secs. 34 and 35, S. bdy., from which no witness trees convenient.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1757-58)

(77.50 chs.)
A Fir 36" dia., at the foot of bluff 30 ft. high for cor. to secs. 34 and 35 marked S35 on E.; T22S R10W on N.; S34 on W.; with 2 notches on E. and 4 notches on W. faces.
I destroy these marks and at
(80.00 chs. West)
A stone in place 5x4x3 ft. which I marked with cross (X) at exact cor. point with 2 notches on the E. and 4 notches on the W. faces, for cor. to secs. 34 and 35, from which
A Fir 28" dia., bears N.80°E., 12 lks. dist. mkd. T22S R10W S35 BT.
A Fir 36" dia., bears S.6°W., 15 lks. dist. mkd. T22S R10W S34 & 35 BT.
A Fir 30" dia., bears N.82°W., 10 lks. dist. mkd. T22S R10W S34 BT.
A large prominent stone, 30 ft. high bears N.20°W., 30 lks. dist. near top of spur.

Survey by Arnold Gibson - For: Oregon State Board of Forestry Dec. 16, 1968 - C.S. File 55/101-6

Original stone 5'x4'x8' found with 4" X, 8" from the North end and 4 notches on the West, from which
28" Fir bears N.80°E., 12 lks.; now 28" burned windfall, scribes T S R O B visible.
36" Fir bears S.6°W., 15 lks.; now a 52" windfall.
30" Fir bears N.82°W., 10 lks.; now a 36" windfall.
Stone 3' high bears N.20°W., 30 lks.; now a 30' high bluff in place.
Spur, course N.15°E., bears West 60 lks.; now in place.
Marked 2 notches on the E. of orig. stone 5x4x3 ft., from which:
50" Fir bears N.6°E., 116.0 ft. scribed T22S R10W S35 BT RS 359.
30" bluff bears N.31°W., 15.0 ft. marked XBO.
(Cont. Next Page)

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 442700

PRIMARY CORNER DESCRIPTION So. Sec. cor. for 34 & 35 only, T22-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set 4x4x72 in. white painted cedar post 2 ft. NW. of
cornerstone.
OSBF metal location poster on 50" Fir N.6°E., 116.0 ft.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under
Group #718, surveyed June/Aug 1970 - (DCSO records Vol. 36
Page(s) 14840-41)

The cor. of secs. 34 and 35 only, monumented with the
original sandstone boulder, 5 x 4 x 3 ft. high, mkd. X on top
from which the remaining original bearing trees:

A root hole bears N.80°E., 12 lks. dist. with a down Fir
alongside, 30" dia., with healed blaze.

A root hole bears S.6°W., 15 lks. dist. with a down Fir
alongside 52" dia., with fragmentary scribe marks
visible on partially open blaze.

and a tree of no record:

A Fir 44" dia., bears N.6°E., 167 lks. dist., with
fragmentary scribe marks visible on partially open
blaze.

At the corner point

Set a brass tablet, 3¼" dia., 3½" stem, in drill hole, in
solid rock, with top mkd:

T 22 S R 10 W

S 34 | S 35

S 3

T 23 S R 10 W

1970

from which a bearing object:

A sandstone boulder 25 x 20 x 20 ft. high, bears N.31°W.,
23 lks. dist. mkd. X BO on E. face.

There are no suitable bearing trees available within limits.