

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO records Vol. 7 Page(s) 2710)

Set a Cedar post, 5 ft. long, 5 ins. dia., 20" in ground for the 1/4 sec. cor. between secs. 34 & 35, from which
A Cedar, 10" dia., bears N.78°E., 64 lks.
A Fir, 18" dia., bears N.23°W., 18 lks.

Fd. Ok on GL0 resurvey and retracement by Levi C. Walker under contract #763, dated Aug. 23, 1905 - (DCSO records Vol. 7 Page(s) 2750)

Douglas Co. Surveyors Office - Gary Langlitz - Pete Earle - Feb. 13, 1975 - C.S. File 57/17-19

A diligent search of the area was made, based on a request from the Coos Bay District of BLM. Several trees in the vicinity have been previously opened. We check the work previously done and open some of the trees further. We find apparent cruiser's marks on one tree which are approx. 40 years old. We do not find any evidence of orig. BT marking. We do not monument this corner.

Jerry Estabrook - Crew: Blue James, Jack Jarrett & Daniel Tlemissen - 12/15/2020 - C.S. 65/109-5

Found - A steel fence post 1.5' high, unknown record
A 48" Fir stump with w nail in open face bears S.28°E., 41.3'.
A 48" Fir stump with w nail in open face bears S.47°W., 61.0'.
A 36" rotten fir stump with no visible marks bears N15'W 11.9'.
New - A 5/8" X 30" iron rod with yellow plastic cap marked "ESTABROOK LS2703". Set along side steel fence post.
A 13" Fir, face scribed "W1/4 S35 BT" with x- chop and tag bears S.82°E., 3.6' to a spike at side center
A 15" Fir, face scribed "E1/4 S34 BT" with x-chop and tag bears S.22°W., 12.0' to spike at side center
A 17" Hemlock, face scribed "E1/4 S34 BT" with x-chop and tag bears N.83°W., 17.7' to spike at side center.
A 13" Fir, face scribed "E1/4 S34 BT" with x-chop and tag bears N.24°W., 20.0' to spike at side center
Continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

Locations & Comments -

LAT. and LONG. per GARMIN ETREX hand held GPS

N: 43°31'24.5" W: 123°51'19.3"

Note - It appears that Weyerhaeuser personnel fd original evidence and perpetuated this corner in Sept. 1970 and in April 1977 per Weyerhaeuser corner records. (Attached to corner report)
Compass Declination 18° East