

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO records Vol. 7 Page(s) 2711)

Set a Fir post, 5 ft. long, 5 ins. dia., 20" in ground for the 1/4 sec. cor. between secs. 26 & 27, from which
A Hemlock, 6" dia., bears S.75°E., 6 lks.
A Hemlock, 5" dia., bears N.62°W., 7 lks.

GLO resurvey and retracement by Levi C. Walker under contract #763, dated Aug. 23, 1905 - (DCSO records Vol. 7 Page(s) 2751)

I make diligent search for the 1/4 sec. cor. but can find no trace of it.
Set a Fir post, 3 ft. long, 4 ins. dia., 24" in ground for the 1/4 sec. cor. mkd. 1/4 S27 on W & 26 on E face, from which
A Fir, 8" dia., bears N.65°E., 9 lks., mkd: 1/4 S26 BT.
A Fir, 8" dia., bears N.65°W., 34 lks., mkd: 1/4 S27 BT.
Again I make a careful search but can find no evidence of the old 1/4 sec. cor.

Gregory K. Miller L.S. #2004 - For: Champion International Corp. - June thru Oct. 1984 - M 97-68 & C.S. 58/146-8

Found - 24" Fir stump. Opened face & found a scribed "T". Also found rotted Fir stump close to position of orig. of orig. NW BT (no scribing found) could not position from record distances. The NE BT, being a flat pull of short distances, was held at record bearing and distance to:
24" Fir stump bears N.65°E., 5.9 ft. (scribed "T" visible) 1906 BT.
25" Fir stump bears N.69°W., 25.9 ft. (1906 rec. N.65°W., 22.4 ft)
Set - 2 1/2" brass cap attached to a 2 1/2"x30" IP with flared bottom & mkd: T23S R10W 1/4 S27 S26 1984 RPLS 2004.
6" Fir bears N.4°E., 25.6 ft. scribed 1/4 S26 BT.
6" Fir bears S.63°W., 21.8 ft. scribed 1/4 S27 BT.

Ron Quimby - Crew: N. Fromdahl, J. Leonard & R. Olson - 3/2016 - C.S. File 65/93-16

Found - 2 1/2" brass cap (properly mkd)
24" Fir stump N.65°E., 5.9 ft., scar.
25" Fir stump N.69°W., 25.9 ft., scar.
18" Fir N.4°E., 25.6 ft., good scar.
20" Fir S.63°W., 21.8 ft. good scar.
cont. next pg

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New - 12" Fir N.18°W., 8.2 ft. scribed ¼ S27 BT.
12" Fir S.6°W., 15.0 ft. scribed ¼ S27 BT.
Compass decl. 16½°E.