

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO records Vol. 7 Page(s) 2711)

Set a Fir post, 4 ft. long, 5 ins. dia., 18" in the ground for the corner to secs. 22, 23, 26 & 27, from which
 A Fir, 6" dia., bears N.88°E., 28 lks.
 A Fir, 6" dia., bears S.80°E., 10 lks.
 A Fir, 7" dia., bears S.70°W., 28 lks.
 A Fir, 8" dia., bears N.2°W., 23 lks.

GL0 resurvey and retracement by Levi C. Walker under contract #763, dated Aug. 23, 1905 - (DCSO records Vol. 7 Page(s) 2726-7)

In place of the old cor. I
Set a Fir post, 3 ft. long, 4 ins. dia., 24" in the ground for the corner to secs. 22, 23, 26 & 27, marked T23S S23 on NE., R10W S26 on SE., S27 on SW., and S22 on NW face, with 2 notches on S & E edges witnessed as described by the Surveyor General. The BT in sec. 26 being dead I mark a new BT as follows:
 A Fir, 8" dia. bears S.75°E. 22 lks. mkd: T23S R10W S26 BT

Arnold Gibson, Oregon St. Board of Forestry - Donald L. McConnell - April 13, 1962 - C.S. File 42/422-9

Found - Orig. post, now missing, from which a:
 6" Fir bears N.88°E., 28 lks., now 8" uproot, point falls in slid out area, BT out of place downhill, scribes S23 BT visible.
 6" Fir bears S.80°E., 10 lks., now missing.
 7" Fir bears S.70°W., 28 lks., now 10" uproot with lower roots still in place, scribes T23 W S27 visible.
 8" Fir bears N.2°W., 23 lks., now missing.
Restoration by Levi C. Walker, May 1906
 Fir post, now missing, from which a: 8" Fir bears S.75°E., 22 lks., now missing.
Set - 3" brass cap mkd: "Ore. St. Bd. of Forestry T23S R10W S22 S23 S26 S27 1962 RS359" in mortar on a sandstone projection of which 3'x4'x2' is exposed and from which a:
 14" Maple bears N.40°E., 70.1 ft., scribed: T23S R10W S23 BT.

continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor Secs 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

20" Fir stump S.58½°W., 96.5 ft., scribed: T23S R10W S27 BT RS359.
20' wide & 15' high sandstone face bears N.86°E., 13.4 ft., mkd: X B0 on Westerly edge.
Ore. State Forestry Dept. metal location poster on 8" Maple N.87°E., 21.0 ft.
4"x4"x72" White painted cedar post 2.5 ft. NW of corner point.

Fd. Ok by G. Miller, 4/1983 M95-29

Ron Quimby - Crew: N. Fromdahl, J. Leonard & R. Olson - 3/2016 - C.S. File 65/93-15

Found - 3" brass cap (properly mkd) mortared into sandstone 3'x4'x2'
26" maple N.40°E., 70.1 ft. good scar.
20" fir snag (8' high) S.58½°W., 96.5 ft vis scribes
20'x15' sandstone face N.86°E., 13.4 ft. mkd X B0 on west face.
OR State forestry location tag on 20" maple N.87°E., 21.0 4"x4"x72" white cedar post 2.5 ft. NW
New - 16" hemlock S.86°W. 12.4 ft scribed T23S R10W S27 BT
Compass decl. 16½°E.