

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T22-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 4 Page(s) 1741)

Set a Fir post 5 ft. long, 5" dia., 20" in the ground for the ¼ sec. cor. on the S. bdy. of Sec. 35, from which,
A Fir 48" dia., bears N.40°E., 38 lks. dist.
A Fir 48" dia., bears S.70°W., 54 lks. dist.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1757)

(38.00 chs.)
A Post set firmly 2 ft. above ground for ¼ sec. cor. on S. bdy. Sec. 35 marked ¼ S on N. face, from which,
A Fir 48" dia., bears N.40°E., 35 lks. dist. mkd. ¼ S BT.
A Fir 48" dia., bears S.70°W., 54 lks. dist. mkd. ¼ S BT.
I destroy this corner and at:
(40.00 chs. (West))
Set a post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which,
A Fir 10" dia., bears N.80°E., 21 lks. dist. mkd. ¼ S BT.
A Maple 16" dia., bears S.71°E., 13 lks. dist. mkd. ¼ S BT

GLO survey by Levi C. Walker, Deputy Surveyor, under Contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2740)

Intersect N. bdy. of Tsp. 1.36 chs. S.89°04'W., of ¼ sec. cor. on S. bdy. of sec. 35, which is a decayed Fir post marked and witnessed as described by the Surveyor General.
I destroy this old post and at the same point,
Set a New Fir post 3 ft. long, 5" sq., 24" in the ground, marked ¼ S35 on N. face.

Survey by Arnold Gibson and Elbert Driver - Wit: Dennis Bagger, Derald Timmons and Ron Witham - For: Oregon State Board of Forestry - Feb. 24, 1958 - C.S. File 42/341

Original post now missing, from which
10" Fir bears N.80°E., 21 lks., now 23", scribe ¼ S visible, also scribed ¼ S35 22S RW visible above orig. face.
16" Maple bears S.71°E., 13 lks., now 28", face unexposed.
Restored by Levi Walker Aug. 1906.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T22-10

Alias	Description

Post found rotted and down, position of scribed R10W visible.
Set 1½" x 36" galv. Iron pipe with 3" bronze cap marked "Ore. St. Bd. of Forestry ¼ S35 1958 RS 359", 33" in ground, in mound of stone, and from which a
34" Fir bears N.2½°W., 67.0 ft. scribed ¼ S35 BT RS 359. OSBF metal location poster on orig. 10" Fir BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #718, surveyed June/Aug 1970 - (DCSO records Vol. 36 Page(s) 14839-40)

The ¼ sec. cor. of sec. 35 only, perpetuated and recorded by the OSBF in 1958, monumented with an I.P. 1½" dia., firmly set, projecting 4" above ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd: 1/4 S 35
1958

from which the original bearing trees:
A Fir stump 28" dia., bears S.83°E., 21 lks. dist. with scribe marks 1/4 S visible on partially open blaze. (Rec. N.80°E.)
A root hole bears S.54°E., 13 lks. dist. with a down Maple alongside, 32" dia., no marks visible. (Rec. S.71°E.) and a bearing tree mkd. by the OSBF:
A Fir 40" dia., bears N.2½°W., 101 lks. dist. with healed blaze.
and new bearing trees:
A Hemlock 9" dia., bears N.38¼°E., 57½ lks. dist., mkd. ¼ S35 BT.
A Hemlock 7" dia., bears N.67½°E., 54½ lks. dist. mkd. X.

Fd. OK, Jan. 1982 by R. Hintz - M 91-1

Survey by Richard Hintz - For: International Paper Co. - June 1983 - M 94-48

Found - 1970 BLM iron pipe with brass cap.
20" Maple, sawed stump, bears N.33°15'E., 32.3 ft. 1970 BT.
Set 50 d. nail in top, center of Maple stump.
Set 5/8" x 36" Iron rod with stamped cap "P.L.S. 497" in top center of a 48" sawed Fir stump which bears N.56°00'E., 18.90 ft.

(Cont. Next Page)

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 502700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only, T22-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Oregon Dept. of Forestry - Lloyd D. Smith, L.S. 1101 - Tim Van Vleet - Sept. 1996 - C.S. File 65/8-10

Found - Oregon State Board of Forestry Pipe & cap in place (1958).
 10" fir, bears N.80°E., 21 lks., **now** 23"x5' high stump S.83°E., faces exposed scribes visible. (Orig. BT. 1894)
 34" Fir bears N.2½°W., 67.0'; **now** 34"x3½' high stump badly decomposed, scribes visible. (1958)
 9" Hemlock bears N.38¼°E., 57½ lks.; **now** 25" in place, face closed BLM bearing tree tag. (1970)
 7" Hemlock bears N.67½°E., 54½ lks.; **now** 16" in place, face closed BLM bearing tree tag. (1970)

New Accessories -
 Orange carsonite marker CBM-250 labeled witness post bears N.44°E., 2.15' to base.
 Orange carsonite marker CBM-250 labeled witness post bears N.51°W., 2.60' to base.

Note - Magnetic Variation 20½° East.