

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 534600

PRIMARY CORNER DESCRIPTION North ¼ Sec. 11 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Levi C. Walker under contract #763, dated Aug. 23, 1905 - (DCSO records Vol. 7 Page(s) 2737)  
-----  
Set a Fir post, 3 ft. long, 4' sq., 24" in the ground, for ¼ sec. cor. on N bdy of sec. 11, marked ¼ S on N & 11 on S face, from which  
    An Alder, 8" dia., bears S.88°W., 7 lks., mkd: ¼ S11 BT.  
    An Alder, 8" dia., bears N.19°W., 15 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - For: "West Shore Lodges Subdivision, Mr. Rose & Mr. Lee - Feb/May 1958 - M 8-72 & C.S. 49/90 (pg 7)  
-----  
No positive identification of OBTs found. See CS file for determining position of this cor.  
Set - Brass cap mkd: County Surveyors Office, 1958  
                                N ¼ S11           T23S R10W  
    13" Hemlock bears S.85°W., 22.3 ft. scribed ¼ S11 CS BT  
    7" Hemlock bears S.68½°E., 40.7 ft. scribed ¼ S11 CS BT

James McIntosh, Oregon Dept. of Forestry - 7/2010 - M161-15  
-----  
Found - DCSO 1½" galvanized iron pipe & bronze cap, 1958 (In place)  
    13" Hemlock S.85°W., 22.3' (now 31" in place, face closed, added BT Tag)  
    7" Hemlock S.68½°E., 40.7' (now 29" in place, face closed, added BT Tag)  
Rewitnessed -  
    Orange carsonite marker CBM-250 labeled WP S.42°E., 2.90' to base.  
    Orange carsonite marker CBM-250 labeled WP S.23°W., 2.95' to base.