

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO records Vol. 7 Page(s) 2711)  
-----  
Set Maple post, 5 ft. long, 5 ins. dia., 20" in ground for the ¼ sec. cor. between secs. 23 & 26, from which  
    A Maple, 30" dia., bears N.50°E., 20 lks.  
    A Maple, 30" dia., bears S.85°E., 30 lks.

Gregory K. Miller L.S. #2004 - For: Champion International Corp. - April/Aug. 1983 - M 95-29 A&B  
-----  
Found - 42" Maple log o ground next to a 42" Maple stump. Log has a face with a portion of scribed "S" visible. Stump has a corresponding face but no scribing visible.  
Set - 2½"x30" IP with 2½" brass cap properly mkd: and with RPLS 2004 stamped.  
    42" Maple stump bears N.50°E., 13.2 ft. (1879 BT)  
    11" Alder bears S.53°E., 48.2 ft. bark scribed ¼ S26 BT  
    13" Hemlock bears S.58°W., 60.9 ft. scribed ¼ S26 BT

James M McIntosh, Oregon Dept. of Forestry - 4/2004 - C.S. File 65/49-31  
-----  
Found - Orig. BTs:  
    30" Maple N.50°E., 20 lks., now 30"x4 ft. high rotted stump in place, no marks visible.  
    30" Maple S.85°E., 30 lks., missing.  
1983 Info:  
    2½" galv. IP with 2½" brass cap (1983) from which a:  
    11" Alder S.53°E., 48.2 ft.; now 16" in place, bark scribes visible. 1983  
    13" Hemlock S.58°W., 60.9 ft., now 16" in place, face closed. 1983  
    Both BTs have Champion Timberlands BT tags.  
New - Carsonite witness post N.32°W., 2.5 ft. to base.  
    Carsonite witness post N.44°E., 2.7 ft. to base.  
    Metal fence post West 1.1 ft.; no record.  
    Metal fence post N.41°E., 1.6 ft.; no record.  
Magnetic decl. 20°E

Ron Quimby - Crew: N. Fromdahl, J. Leonard & R. Olson - 3/2016 - C.S. File 65/93-17  
-----  
Found - 2½" brass cap (properly mkd)  
    30" rotten maple stump N.50°E., 13.2 ft. (1879 BT)  
continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 17" Alder S.53°E., 48.2 ft., bark scribes.  
18" Hemlock S.58°W., 60.9 ft. good scar.  
Carsonite posts N.32°W., 2.5 ft. & N.44°E., 2.7 ft.  
Steel fence post west 1.1 ft. & N.41°E., 1.6 ft.  
30" Maple N.81°E., 50.8 ft. scribed ¼ S23 BT.  
8" Fir N.26°W., 40.7 ft. scribed ¼ S23 BT.  
Compass decl. 16½°E.