

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO records Vol. 7 Page(s) 2713)  
-----  
Set a Maple post, 5 ft. long, 5 ins. dia., 20" in ground for the 1/4 sec. cor. between secs. 14 & 23, from which  
    A Cedar, 24" dia., bears N.45°E., 8 lks.  
    A Cedar, 16" dia., bears S.85°W., 24 lks.

Arnold G. Gibson, Oregon St. Bd. of Forestry - Dec. 1972 - M 49-20  
-----  
1/4 corner reestablished  
Set - OSBF iron pipe with 3" bronze cap 36" in ground.  
    11" Fir, N.31°E., 10.8 ft. (RS359)  
    9" Fir, S.1°E., 8.3 ft. w/yellow metal location poster.  
    4"x4"x72" white painted Cedar post N.50°E., 3.0 ft.