

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 292 survey dated Aug. 7, 1878 (DCSO records Vol. 4 Page(s) 1741)

Set a Fir post 5 ft. long, 5" dia., 20" in the ground for the 1/4 sec. cor. on N. bdy. of Sec. 2, from which,
A Fir 48" dia., bears S.80°W., 15 lks. dist.
A Fir 24" dia., bears N.75°W., 35 lks. dist.

GL0 survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1757)

Find a post 3" dia., firmly set 2 ft. above ground for 1/4 sec. cor. on N. bdy. sec. 2, T23S R10W, marked 1/4 S on N. face, from which,
A Fir 48" dia., bears S.80°W., 15 lks. dist. mkd. 1/4 S BT.
A Fir 24" dia., bears N.75°W., 35 lks. dist. mkd. 1/4 S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Jan. 23, 1958 - C.S. File 42/331-3

Found original Post, rotted off, ground level, scribes 1/4 S S2 T22S R10W visible, from which a:
48" Fir bears S.80°W., 15 lks.; now 50" snag, bark scribes 1/4 S BT visible, also not original, bark scribes 1/4 S S2 T22S R10W visible.
24" Fir bears N.75°W., 35 lks.; now 36" stump, face unexposed.
Set 1 1/2" x 36" galv. Iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FOREST 1/4 S2 1958 RS 359", 33" in ground, and from which a:
22" Hemlock bears S.16°E., 15.6 ft.; scribed 1/4 S 2 BT RS 359.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #718, surveyed June/Aug 1970 - (DCSO records Vol. 36 Page(s) 14839)

The 1/4 sec. cor. of sec. 2 only, perpetuated and recorded by the OSBF in 1958, monumented with an iron post 2" dia., firmly set, projecting 2" above ground, with brass cap mkd:

1/4 S 2
1958

from which the original bearing trees:
(Cont. Next Page)

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir snag 58" dia., bears S.80°W., 15 lks. dist., with scribe marks S2 1/4 T23S R10W visible on bark blaze.
A Fir stump 36" dia., bears N.75°W., 35 lks. dist., with healed blaze.