

PRIMARY CORNER DESCRIPTION Cor. Secs. 35 & 36 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO recs. Vol. 7 Page(s) 2699-2700)

Set an fir post, 5 ft. long, 5" dia., 20" in the ground, for cor. of secs. 1, 2, 35, & 36, from which
A fir, 30" dia., bears N.70°E., 95 lks.
A fir, 24" dia., bears S.80°E., 106 lks.
A fir, 24" dia., bears N.52°W., 78 lks.
A fir, 24" dia., bears N.52°W., 78 lks.

Donald Peel - March 1967 (added 7/20/2015) - C.S File 55/30-1

Found - Post gone
30" fir, N.70°E., 95 lks., fd but BT was a blow down & has been bucked off - - face visible on under side.
24" fir, S.80°E., 106 lks., fd 24" fir snag, bark scribed - - scribe visible.
24" fir S.20°W., 76 lks and 24" fir N.52°W., 78 lks. destroyed 1896.
Set hub for corner and re-referenced with "W" nails & Weyerhaeuser tag.
32" fir N.62°E., 60.0 ft.
26" fir stump, N.32°W., 93.5 ft.
"W" nail n rock cut bank, N.61°W., 35.6 ft.

Tony Hostetter - For: Weyerhaeuser - May 2015 - C.S. 65/88-9

Found - 2 BTs and a tag on a rock face listed in 1967 survey by D.L. PEEL (C.S. 55/30-1), which indicates that 2 original BTs were found.
Set - 5/8" iron rod, w/plastic cap marked "HOSTETTER LS 1975" on edge of gravel road based on Peel's BT Information. From which:
42" Fir stump, WEYCO tag, bears; N.61°36'E, 60.0' to "W" nail, Peel record: N.62°E., 60.0 ft.
Tag on rock face, bears; N.59°11'W., 35.6 ft, Peel record: N.61°W., 35.6 ft.
26" fir stump, WEYCO tag, bears; N.32°41'W., 93.6' to "W" nail, Peel record: N.32°W., 93.6 ft.
New BTs- 12" Fir, scribed "S36 SW BT, BT tag, bears; N.28°38'E., 14.2' to spike.
10" fir, scribed "S35 SE BT", BT tag bears; S.20°42'W., 90.3 ft to spike.

Fd 5/8" IR as described in 2015 T. Hostetter 4/2019 C.S. 65/103-7