

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO recs. Vol. 7 Page(s) 2703)  
-----  
Set Maple post, 4 ft. long, 5 ins. dia., 18" in ground for the 1/4 sec. cor. between secs. 25 & 26, from which  
    A Maple, 12" dia., bears East, 57 lks.  
    A Fir, 40" dia., bears West, 70 lks.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/16/1933 - FB 119 Pg11 (C.S. 49/79-80-1 pg 8)  
-----  
No trace of 1/4 cor. found.

Gregory K. Miller, LS #2004 - For: Champion International Corp. - June/Oct. 1984 - M 97-68 and C.S. File 58/146-7  
-----  
Found - 58" Fir stump with bark scribed "BT" visible. I accept this as the orig. 1879 Fir BT.  
        The orig. Maple is missing.  
Set - At record bearing & dist. from the Fir BT (stump) I set: A 2 1/2" brass cap attached to a 2 1/2" x 30" galv. IP with flared bottom and mkd: T23S R10W 1/4 S26 S25 1984 RPLS 2004.  
Accessories -  
    58" Fir stump bears due West 46.2 ft. (1879 BT)  
    37" Cedar stump bears N.67°E., 11.7 ft. (not of rec.) scribed T22S S26W)  
New BTs- 16" Fir bears N.12°E., 19.3 ft. (1984 BT) 1/4 S25 BT.  
          18" Fir bears N.82°W., 24.0 ft. scribed 1/4 S26 BT.  
Note - Due to the upcoming logging operations, I have removed and have in my possession the piece of bark with the scribed "BT" visible. I will replace it after operations are completed.

Fd. Ok by T. Hostetter, 8/1996 M 126-31