

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO recs. Vol. 7 Page(s) 2703)

-----  
Set Yew post, 4 ft. long, 5 ins. dia., 18" in the ground for the corner to secs. 23, 24, 25 & 26, from which  
A Fir, 24" dia., bears N.60°E., 20 lks.  
A Fir, 72" dia., bears S.45°E., 5 lks.  
A Fir, 16" dia., bears S.75°W., 11 lks.  
A Hemlock, 16" dia., bears N.50°W., 43 lks.

Oregon St. Forestry Dept., Arnold G. Gibson - Witnesses:  
Kucera & Fitch - Sept. 2, 1967 - C.S. File 55/50

-----  
Original - Post (found wood remains in orig. square post hole, also found a scribed post & stub in ground, probably Elliott survey) from which a:  
24" Fir bears N.60°E., 20 lks.; now a 12"x8' stub  
72" Fir bears S.45°E., 5 lks.; now a 70" buckskin snag.  
16" Hemlock bears N.50°W., 43 lks.; now missing.  
16" Fir bears S.75°W., 11 lks.; now rotted to ground level.  
Set - 1½"x36" galv. iron pipe with 3" br. cap mkd: Ore. St. Board of Forestry T23S r10W S23 S24 S25 S26 1967 RS 359, 32" in ground & from which a:  
13" Fir bears N.26°E., 34.2 ft. to face; scribed T23S R10W S24 BT.  
12" Fir bears S.01°E., 22.8 ft., scribed: T23S R10W S25 BT.  
8" Bowed Fir bears S.56°W., 19.4 ft., scribed: T23S R10W S26 BT.  
15" Fir bears N.64°W., 37.5 ft., scribed: T23S R10W S23 BT RS 359  
36" Fir stump bears S.71dw., 14.6 ft., found portion of scribes BT - probably Elliott survey.  
4"x4"x72" White painted Cedar post 1.5 ft. W of corner pipe.  
Oregon St. Forestry Dept. metal location poster on 72" snag. (Orig. 72" Fir SE)

Fd. Ok by L. Smith, 9/29/1981 M89-40  
Fd. Ok by L. Smith, 12/1994 M121-25