

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO recs. Vol. 7 Page(s) 2704-5)  
-----  
Set a Yew post, 4 ft. long, 5 ins. dia., 18" in the ground for the corner to secs. 13, 14, 23 & 24, from which  
    A Hemlock, 10" dia., bears N.85°E., 24 lks.  
    A Fir, 30" dia., bears S.25°E., 67 lks.  
    A Hemlock, 16" dia., bears S.45°W., 16 lks.  
    A Hemlock, 20" dia., bears N.30°W., 40 lks.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/1933 - FB 119 Pg. 45 (C.S. 49/79-80-1 pg 8)  
-----  
Found old yew post & OBTs. Reset cor. post with a 4"x4"x4' Fir post from which  
    A 24" Hemlock, bears N.85°E., 24 lks.  
    A 48" Fir, bears S.25°E., 67 lks.  
    A 24" Hemlock, bears S.45°W., 16 lks.  
    A 30" Hemlock, bears N.30°W., 40 lks.

Oregon St. Forestry Dept., Arnold G. Gibson - Witnesses: Kucera & Fitch - Sept. 2, 1967 - C.S. File 55/50  
-----  
Orig. - Post (now missing) from which a:  
    10" Hemlock bears N.85°E., 24 lks., portions of root system remaining.  
    30" Fir bears S.25°E., 67 lks., found bark scribes T23S R10W BT, believed to be Elliot survey.  
    16" Hemlock bears S.45°W., 16 lks., 30" windfall, face buried.  
    20" Hemlock bears N.30°W., 40 lks., portions of rotted stump remaining.  
Set - 1½"x36" galv. iron pipe with 3" bronze cap mkd: Ore. St. Bd. of Forestry S13 S14 S23 S24 1967 RS 359, 34" in ground, from which a:  
    20" Hemlock bears N.29°W., 29.2 ft. to face, scribed: T23S R10W S14.  
    20" Hemlock bears S.39°E., 30.6 ft. to face scribed: T23S R10W S25.  
    30" Cedar bears S.01°W., 25.1 ft., to face, scribed: T23S R10W S23 BT.  
    6" Alder bears N.80°E., 13.3 ft., bark scribed: T23S R10W S13 BT.  
    4"x4"x72" WPCP 1.0 ft. E. of corner pipe.  
    Ore. St. Forestry Dept. metal location poster on 30" Cedar S.01°W., 25.1 ft.  
    Elliott State bdy sign & line blazes on 30" Cedar.

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. & used on BLM Resurvey by Donald Beck, Cadastral Surveyor, under Group #658, surveyed Oct/Nov. 1967 (DCSO records Vol. 36 Page(s) 14605-6)

Fd. Ok by Lloyd Smith, 9/29/1981 M 89-40  
Fd. Ok 9/1983 M 95-55  
Found OK by R. Ward, May 2002 - 2002-0027 A & B  
Fd. ok by J. McIntosh - Aug. 2004 M145-50