

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO recs. Vol. 7 Page(s) 2705-6)

Set a Fir post, 5 ft. long, 5 ins. dia., 20" in ground for the 1/4 sec. cor. between secs. 13 & 124, from which
 A Fir, 8" dia., bears S.45°E., 29 lks.
 A Fir, 6" dia., bears S.38°W., 27 lks.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/1933 - FB 119 Pg47

Could find no trace of 1/4 cor. or BTs so set a 4"x4" Red Cedar post 2' in ground from which
 A 15" Hemlock bears S.25°E., 22' dist.
 A 10" Alder bears N.72°E., 21' dist.
Set corner post at 26+02 ⁰² on true line between sec. cors. 13, 14, 23, 24 and 11, 12, 13, 14. True line being 69.5 ft. West of our line.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M. Godfrey - S. Bilow - Feb. 11, 1958 - C.S. File 49/63-2

Found - 4"x4" sq. & scribed stake at corner & both BTs as scribed by State. No trace of orig. BTs can be found.
 This corner proportioned by State.
 Find State's 15" now 30" Hemlock, open face shows good scribing, bears S.65°E., 22.0 ft. (State S.25°E., 22.0 ft.)
 10" now 18" Alder snag, checks State's bearing & dist.
Set - Brass cap alongside sq. stake, mkd: County Surveyors Office, 1958, 1/4 S14/S13 T23S R10W
 I reblaze & rescribe 30" Hemlock S.65°E., 22.0 ft. 1/4 S13 CS BT.
 I blaze & scribe 10" Hemlock N.24°W., 21.0 ft. 1/4 S14/S13 CS BT.

Fd. & used on BLM Resurvey by Donald Beck, Cadastral Surveyor, under Group #658, surveyed Oct/Nov. 1967 (DCSO records Vol. 36 Page(s) 14606)

Fd. Ok by A. Gibson, 12/1972 M 49-20
Fd. Ok by G. Miller 9/1983 M 95-55
Fd. Ok by R. Ward 12/1997 M 128-25

continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. & used on BLM dependent resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group # 1459, surveyed Aug.. 1988 - (DCSO records Vol. 49 Page(s) 18732)

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/5/2019 (Filed 11/18/2021) - C.S. File 67/50-36

Found - 1958 DCSO 2½" BC on a 1" I.D. IP, monument is 20" below surface. Cap is marked as described. Monument is under east edge of small fir stump, sawn flush with ground.

A 43" dia., x 4 ft tall hemlock stump, which is opened to find the rescribe "¼S"; bears S.65°E., 22.0 ft. (as per 1958 renewal rec) 1933 CCC

From the 1958 DCSO renewal evid. of the renewal tree; now a root depression fd at record pos.

New - A multi-trunk alder, the most SW'ly 11" dia., trunk which is scribed "¼S13" "CSBT" on a double blaze; center of root crown bears N.42½°E., 13.0 ft.

A 32" dia., R.Cedar, scribed "¼S13" "CSBT" on a double blaze; bears S.81°E., 21.1 ft.

A 9" dia., D.Fir, scribed "¼S14CS" "BT" on a double blaze; bears S.68°W., 8.4 ft.

Note - Compass decl. 15°E.