

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars under contract #292, dated August 7, 1878 - (DCSO records Vol. 7 Page(s) 2706

Set Maple post, 5 ft. long, 5 ins. dia., 20" in the ground for the corner to secs. 11, 12, 13, & 14, from which
A Maple, 6" dia., bears N.72°E., 17 lks.
A Fir, 8" dia., bears S.43°E., 56 lks.
A Maple, 6" dia., bears S.40°W., 32 lks.
A Maple, 8" dia., bears N.30°W., 20 lks.

GL0 survey by Levi C. Walker under contract #763, dated June 20, 1905 - (DCSO records Vol. 7 Page(s) 2754-5)

The old post being gone, by reference to the BTs I relocate the point where it stood, where I: Set a Fir post, 3 ft. long, 4" sq. 24" in the ground, for cor. secs., 11, 12, 13, & 14, marked T23S S12 on NE, R10W S13 on SE, S14 on SW & S11 on NW face, with 4 notches on S & 1 notch on E edge; witnessed as described by the Surveyor General.

Elliott State Forest Corner Records by Federal Civilian Conservation Corp (CCC) 8/1933 - FB 19 Pg49 (C.S. 49/79-80-1 pg 9)

Found - Old corner post & one orig. BT replaced old post with a 4"x4"x4' Fir post, from which
A 30" Fir, bears S.43°E., 37.0 ft. (Orig.)
New BTs- A 36" Fir bears S.10°W., 42.0 ft.
A 30" Fir bears N.84°W., 20.1 ft.
A 30" Fir bears N.65°E., 3.2 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - M. Godfrey - S. Bilow - Feb. 11, 1958 - C.S. File 49/63-1

Found - Rotted base of stump that checks bearing & distance for orig. SE BT. Also find all BTs scribed by State 1933-193
The SW BT now 36" stump only shows good scribing.
Find 30" now 36" Fir N.78°W., (State N.48°W.) 21.7 ft. shows good scar. I do not open.
Find 30" now 36" Fir N.65°E., 5.0 ft., shows good scar, part of face open, scribing visible.
Also find 4"x4" scribed stake at corner.
Set - Brass cap at corner mkd S11|S12 T23S R10W County
S14|S13 Surveyor's Office,
1958
18" Fir bears S.44½°W., 73.5 ft. scribed S14 T23S R10W CS BT. continued next page

TOWNSHIP 23 RANGE 10 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

| |
|---|
| 18" Maple bears S.71°E., 10.0 ft., mkd: S13 T23S R10W CS BT. |
| Fd. & used on BLM Resurvey by Donald Beck, Cadastral Surveyor, under Group #658, surveyed Oct/Nov. 1967 (DCSO records Vol. 36 Page(s) 14607) |
| John Minor - For: Menasha Corp. - 9/1990 - C.S. File 63/104-23 ----- Remonumented corner from the remaining BT: Corner is 1½" brass cap affixed to a 1¼"x36" iron pipe driven 32" into the ground. Cap is stamped "T23S R10W S11 S12 S13 S14 LS 2052 1990" from which: 47" (formerly 36") D.Fir stump bears N.78°W., 21.7 ft. 27" Hemlock snag bears N.6°E., 39.4 ft. 37" D.Fir stump bears S.16°W., 42.8 ft. 18" Maple bears S.7°E., 36.6 ft. |
| Lloyd Smith, for Oregon State Dept. of Forestry, Dec. 1997 - M 128-17 ----- Section Corner for 11, 12, 13 & 14 Found - 1¼" iron pipe with brass cap, 1990 (in place with Douglas Co. Surveyor's Office brass cap w/iron pipe alongside out of ground) 42" Fir, (DCSO) N.78°W., 21.78 ft. (now 43" x 3 ft. high stump in place, face closed, bearing tree tag visible). 48" Fir stump, (DCSO) S.11°W., 42.90 ft. (now 32" x 3 ft. high stub in place, bearing tree tag visible). 40" Fir stump, (orig.) S.43°E., 36.96 ft. (now 27" x 3 ft. high stump in place, face chopped out, no scribes visible). 18" Maple, (1990) S.07°E., 36.6 ft. (now 20" dying Maple in place, bearing tree tag visible). 27" Hemlock snag, (1990) N.06°E., 39.4 ft. (now 24" x 10 ft. high stump in place, face closed, bearing tree tag visible). 48" Fir (DCSO) N.48°E., 5.94 ft. (now windfall, face buried) New Accessories - Orange carsonite marker labeled witness post, bears N.55°W., 4.1 ft. to base. Orange carsonite marker labeled witness post, bears S.61°W., 4.5 ft. to base. |